

# Han 24B Ex-HTE-M32-reel



Part number	19 36 024 1442
Specification	Han 24B Ex-HTE-M32-reel
HARTING eCatalogue	https://b2b.harting.com/19360241442

Image is for illustration purposes only. Please refer to product description.

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han <sup>®</sup> Ex
Type of hood/housing	Hood

### Version

Size	24 B
Version	Top entry
Cable entry	1x M32
Locking type	Single locking lever
Field of application	Connectors for explosion hazardous environments
Details	ATTENTION! Only to be used with Han <sup>®</sup> Ex inserts!

# Technical characteristics

Limiting temperature	-20 +40 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65 With cable gland

## Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 5015 (sky blue)
RoHS	compliant
ELV status	compliant



## Material properties

China RoHS	е
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

### Commercial data

Packaging size	1
Net weight	496.75 g
Country of origin	China
European customs tariff number	85389099
GTIN	5713140163577
eCl@ss	27440202 Shell for industrial connectors