



Picture differs from the item.

Color:

Data

Electrical data

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastraße 27

32423 Minden

Phone: +49 571 887-0 | Fax: +49 571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

Ratings per IEC/EN

Ratings per	IEC/EN 60664-1
Rated voltage (III/2)	800 V
Rated impulse voltage (III/2)	2.5 kV
Rated current	16 A
Legend (ratings)	(III / 2) \triangleq Overvoltage category III / Pollution degree 2

Connection data

Connection points	3
Total number of potentials	3
Number of connection types	1
Number of levels	1

Connection 1

Connection technology	Screw connection
Actuation type	Operating tool
Solid conductor	0.5 ... 2.5 mm ² / 20 ... 14 AWG
Fine-stranded conductor	0.5 ... 2.5 mm ² / 20 ... 14 AWG
Strip length	5 ... 7 mm / 0.2 ... 0.28 inches
Conductor connection direction to PCB	0 °
Pole number	3

Physical data

Pin spacing	5 mm / 0.197 inches
Width	15 mm / 0.591 inches
Height from the surface	11 mm / 0.433 inches
Depth	9 mm / 0.354 inches
Solder pin length	4.5 mm
Solder pin diameter	1 mm

Plug-in connection

Plugging without loss of pin spacing	Yes
--------------------------------------	-----

PCB contact

PCB contact	THT
Solder pin arrangement	over the entire terminal strip (in-line)

Subject to changes. Please also observe the further product documentation!

Number of solder pins per potential

1

Material Data

Note (material data)

Information on material specifications can be found here

Color	gray
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Clamping spring material	Chrome-nickel spring steel (CrNi)
Contact material	Electrolytic copper (E_{Cu})
Contact plating	Tin
Fire load	0.096 MJ
Weight	3.6 g

Environmental requirements

Limit temperature range -60 ... +105 °C

Commercial data

eCl@ss 10.0	27-44-04-01
eCl@ss 9.0	27-44-04-01
ETIM 8.0	EC002643
ETIM 7.0	EC002643
PU (SPU)	300 (100) pcs
Packaging type	box
Country of origin	IN
GTIN	4045454539979
Customs tariff number	85369010000

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	a0dbd928-df72-461b-a7c2-b6abc866ab98

Subject to changes. Please also observe the further product documentation!

SCIP notification number (Belgium)	047ed212-bd7b-40ee-ac18-adb1c34ab632
SCIP notification number (Bulgaria)	8bb63008-c706-4654-82e2-70f3c25772a5
SCIP notification number (Czech Republic)	dfa4d72b-29c4-44f6-8cd3-95f92b23e0da
SCIP notification number (Denmark)	6ce68b1a-d244-41a0-8be7-df5264ddc72f
SCIP notification number (Finland)	2975d0e3-e66a-4452-840c-5efe5e70fee6
SCIP notification number (France)	2aac3f0b-cb61-42d3-834d-86fbb08438a6
SCIP notification number (Germany)	12aecab-4485-431b-9111-6fbeaaeabc8
SCIP notification number (Hungary)	cc922d94-79b9-4e43-86f9-18e6863f9c0e
SCIP notification number (Italy)	6514c34a-c2ee-4e80-ac04-a27b05374146
SCIP notification number (Netherlands)	98408107-0a18-436d-b417-6502f99eb781
SCIP notification number (Poland)	eb3f2cf3-916e-4c4b-8f22-7a9e1878ecb1
SCIP notification number (Romania)	9158eb37-b316-453e-8367-16344cde8706
SCIP notification number (Sweden)	02d7769b-a266-43e0-b7fc-418c1176d804

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	CCA DEKRA Certification B.V.	EN 60947	NTR NL-7137
	CCA DEKRA Certification B.V.	EN 60947	2160584.33
	CSA DEKRA Certification B.V.	C22.2 No. 158	70048844
UL UL International Germany GmbH		UL 1059	E45172

Declarations of conformity and manufacturer's declarations

Logo	Approval	Additional Approval Text	Certificate name
	EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-
	UK-Declaration of Conformity WAGO GmbH & Co. KG	-	-

Downloads

Documentation

Additional Information

2019 年4月3日

pdf

Download

Subject to changes. Please also observe the further product documentation!

CAD/CAE-Data

PCB Design

Symbol and Footprint 237-146

URL

Download

CAx data for your PCB design, consisting of "schematic symbols and PCB footprints", allow easy integration of the WAGO component into your development environment.

Supported formats:

- Accel EDA 14 & 15
- Altium 6 to current version
- Cadence Allegro
- DesignSpark
- Eagle Libraries
- KiCad
- Mentor Graphics BoardStation
- Mentor Graphics Design Architect
- Mentor Graphics Design Expedition 99 and 2000
- OrCAD 9.X PCB and Capture
- PADS PowerPCB 3, 3.5, 4.X, and 5.X
- PADS PowerPCB and PowerLogic 3.0
- PCAD 2000, 2001, 2002, 2004, and 2006
- Pulsonix 8.5 or newer
- STL
- 3D STEP
- TARGET 3001!
- View Logic ViewDraw
- Quadcept
- Zuken CadStar 3 and 4
- Zuken CR-5000 and CR-8000

PCB Component Libraries (EDA), PCB CAD Library Ultra Librarian

CAE data

EPLAN Data Portal 237-146

URL

Download

CAD data

Subject to changes. Please also observe the further product documentation!

2D/3D Models 237-146

URL

Download

Environmental Product Compliance

[Compliance Search](#)

Environmental Product Compliance 237-146

URL

Download

PCB terminal block; 2.5 mm²; Pin spacing 10 mm; 3-pole; 2,50 mm²; gray

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastraße 27

32423 Minden

Phone: +49 571 887-0 | Fax: +49 571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.