


	REVISIONS							
REV	ECO	DESCRIPTION	DATE	BY	APPR			
A1	-	RELEASE NEW DRAWING	28MAR22	VITO	TOMMY			



NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC; BLACK SEAL: SILICONE RUBBER THREADED INSERT: STAINLESS STEEL

2. MODIFICATIONS: BACKSHELL RING ADAPTER (BRA); STANDARD DIA. WIRE SEAL.

SEALED PANEL MOUNT:


- 3. SPECIFICATIONS:
 - 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
 - 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
 - 3.4 MOISTURE RESISTANCE:

IP68(IM OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION);

- IP69K (MATED CONDITION)
- 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDP06-18-06S* (* = SEAL TYPE) (C030 OPTION)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.


6 CONTACT SIZE AND WIRE RANGE:

CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL	CURRENT
SIZE	O.D.	O.D.	WIRE RANGE	RATING
4	6.63 mm (.261in)	7.41mm (.292 in)	6 AWG (16-13mm²)	100 AMPS



RECOMMENDED PANEL MOUNTING HOLE

RECOMMENDED PANEL THICKNESS:1.6 TO 4.7MM



BACKSHELL RING ADAPTER -GREEN

TITLE: 2POS, RECEPT, PIN, PANELMATE AHDP SIZE 18, NORMAL SEAL, BRA, C030

3

£

	AHDP02-18-0	-06PN-BRAC030							3
QUANTITY	PART N	NUMBER		DESCRIPTION		ITEM]-		
			MA	TERI	ALS LI	ST			H
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Toteranese are as follows: 1 PL DEC ±0.16 3 PL DEC ±0.16 3) Note reference = MATERIAL SPECIFICATIONS:		SIG	NATURE	S DATE	1 Amphonol			1	
		DRAWN:	VITO.LI	28MAR22	Amphenol				
		CHECKED:	SULLENZHANO	9 29MAR22	22 Sine Systems - www.amphenol-sine.com		enol-sine.com	_	
		ENGINEER:			44724 Morley Drive				
		APPROVAL:	TOMMY.XIE	30MAR22		Clinton Township, MI 4	8036		4
	WEIGHT: 55.8q		:			2 POS, RECEPTACI			
		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY, DESIGN FEATURES.			PANELMATE AHDP SIZE 18, NORMAL SEAL, BRA, C030				
		B C-	AHDP02-18-06P		A1				
NEXT ASS'Y:			NUFACTURING VARIATIONS.		SCALE: NONE	DURAMATE	SHEET 1 OF	1	1