

6

5

4

3

2

1

DESCRIPTION: YELLOW 16-12 TPE FLEX CABLE

**JACKET:**

COLOR: YELLOW TPE  
DIA: .590" REF.

PRINT LEGEND: 16 AWG 12/C UL TYPE TC-ER 600V 90°C SUNLIGHT RESISTANT OIL RESISTANT II DR AWM 90°C  
600V--- CSA AWM I/II A/B 90°C 600V FT4  
IMPRINT COLOR: BLACK

**CONDUCTOR:**

STRANDING: 65 X #34 BARE COPPER  
INSULATION MATERIAL: NYLON SHEATH OVER POLYVINYL CHLORIDE


**CONSTRUCTION:**

SEPARATOR: TISSUE TAPE, OPTIONAL

MECHANICAL CHARACTERISTICS:

TORSIONAL FLEX TEST	20 MILLION CYCLES PER MIL-C-13777G
BEND FLEX TEST	20 MILLION CYCLES PER MIL-C-13777G
WELD SLAG RESISTANCE	WOODHEAD STANDARD S-300

COLOR ROTATION OF CORD



E

E

D

D

C

C

B

B

A

A

RELEASED EC NO: IPC2016-1158 DRWN: GGUSTAFS 2016/02/23 CHKD: RSTONE 2016/03/16 APPR: BWOODMAN 2016/03/04	DESCRIPTION REV	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE INCH ONLY		SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION		
		$\nabla=0$ $\sphericalangle=0$	mm	INCH	DRAWN BY DATE	TITLE #16/12 YELLOW TPE CABLE					
		4 PLACES	±---	±---	GGUSTAFS 2016/02/23	CHECKED BY DATE					
		3 PLACES	±---	±.005	RSTONE 2016/03/16	APPROVED BY DATE					
				BWOODMAN 2016/03/04	MATERIAL NO. 1302130011		DOCUMENT NO. SD-130213-001		SHEET NO. 1 OF 1		
A			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						

6

5

4

3

2

1