



MATERIALS:

1. GUIDE TRAY - GLASS FILLED POLYBUTYLENE TEREPHTHALATE, STATICALLY DISSIPATIVE, 94V-0, BLACK
2. SHIELD - ZINC DIECAST, CLEAR CHROMATE FINISH
3. DB-9 RECEPTACLE
SHELL: STEEL WITH TIN PLATE
INSULATOR: GLASS FILLED PBT, UL94V-0
CONTACTS: PHOSPHOR BRONZE, 30 MICRO GOLD OVER NICKEL UNDERPLATE
4. ADAPTER CAN BE STACKED SIDE TO SIDE ON A 1.5 INCH MINIMUM SPACING.

WITHOUT SERIAL IDENTIFICATION	73086-0001
DESCRIPTION	PART NUMBER

MFC. SH. REV.	REMOVE P/N	REVISIONS	DIMENSIONS SHOWN (METRIC) INCH	
	PER UOI 2000-0151		UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR 1/2°	
	99/08/09 DSL		INCH	METRIC
			3 PLACE ± .010	---
D	DRWG. BY RKN	CHK'D. BY DLD	2 PLACE ± ---	± .25
	APP'D. MJM	SCALE 2: 1	1 PLACE ---	± ---

TITLE		REVISE ONLY ON CAD SYSTEM	
GBIC ADAPTER COPPER, DB-9, PASSIVE			
PART NO. SEE CHART		DRWG. NO. SDA-73086-001	
FILE NAME S73086X1.DGN	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.		DRG. NO. SDA-73086-001
SHEET NO. 1 OF 1		DATE 98/05/20	
MOLEX INCORPORATED LISLE, ILL. 60532 U.S.A.			