ALL RIGHTS RESERVED. C COPYRIGHT - TE Connectivity E2 REV. ECO-17-011267 1. MUST BE ASSEMBLED WITH CAP REAR P/N 770050-1 BEFORE MATING. KIT P/N IS 770026-1. RECOMMENDED PANEL THICKNESS 0.76-2.29 [.030-.090]. PANEL MUST BE PUNCHED SO THAT THE HOUSING ENTERS THE PANEL IN THE SAME DIRECTION AS THE PUNCH. 4 OPTIONAL FOR KEYING HOUSING IN PANEL. S CIRCUIT NUMBER 1 LOCATION. AMP LOGO LOCATED ONCE ON ANY INDICATED SURFACE FARSIDE. 7. DIMENSIONS SHOWN REPRESENT PRODUCT IN DRY, AS MOLDED, CONDITION. ADDITIONAL 2% GROWTH DUE TO SUBSEQUENT MOISTURE ABSORPTION MAY OCCUR AND SHOULD BE ACCOUNTED FOR. CSA LOGO LOCATED ONCE ON ANY INDICATED SURFACE 27.05 -[1.065]⁻ 4.45±0.25 4.45±0.25 [.175±.010]-- [.175±.010] 2.79 [.110] 8.64±0.25 [1.050] 13.46 ↓ [.340±.010] [.530] 8.13±0.25 [.320±.010] 7.62±0.25 [.300±.010] 2.41±0.25 [.095±.010] 22.99 Î 2.54±0.25 [.100±.010] 6.35±0.25 [.250±.010] 13.21+0.13 .520 +.005 -.010 RECOMMENDED PANEL CUTOUT (HOUSING ENTRY SIDE) SCALE 2:1 \triangle \triangle THIS DRAWING IS A CONTROLLED DOCUMENT. K. SALMON €TE TOLERANCES UNLESS OTHERWISE SPECIFIED: CAP FRONT, 4 CIRCUIT, UNIVERSAL MATE—N—LOK ± -± -± -± 0.13 [.005] ± -± -PRODUCT SPEC APPLICATION SPEC SIZE CAGE CODE DRAWING NO A 1 00779 C-770049 MATERIAL NYLON,UL94V-0, 0.000000 CUSTOMER DRAWING 4805 (1/15) 3D

THIS DRAWING IS UNPUBLISHED.

05SEP2017 HC KR

770049-1 PART NUMBER

RESTRICTED TO

TE Connectivity