



Model: USB-4COMi-SI-M

4 Port USB to Quad RS-422 485 Optically Isolated Adapter

The USB-4COMi-SI-M Serial Adapter instantly adds four RS-422, or RS-485 serial communication ports to your system while offering optical isolation and surge protection.



Specifications

Serial Interface	RS422/485 port, optical isolated
Ports	4
Speed	Up to 921.6kbps
Signals	RS422 TxD+/-, RxD+/-, RTS+/-, CTS+/-, GND RS485 Data+/-, GND
Available Modes	RS422 full duplex, RS485 4-wire, full duplex, RS485 2-wire, half duplex, with echo RS485 2-wire, half duplex, without echo
USB Interface	USB 2.0
Power	External power supply 5V DC required. Adapter included 12V not possible.
Driver	Windows XP, 2003 Server, Vista, Linux (Kernel 2.4 and up built-in)
Connectors	4 DB9 male
Dip Switches	External 4-pin
Dimensions	167 x 99 x 29 mm (WxLxH), 189 x 102 x 30 mm (with DB9 connector and ears)
Environmental	Operating Temperature 0 to 55 °C (32 to 131 °F) Operating Humidity 5 to 95% RH Storage Temperature -20 to 75 °C (-4 to 167 °F)

Features

- DIN-Rail mountable
- 4 x RS422/485 ports
- Optical isolated
- Speed up to 921.6kbps
- External power supply
- Metal case

Product Information

Product Name:	USB-4COMi-SI-M
Packing List:	USB-4COMi SI-M, USB cable 0,9m, Power adapter, CD, English Documentation
Optional Accessories:	N/A