

SA3338-90-18-DP 3.5 GHz MIMO Sector Antenna

Innovative **Technology** for a **Connected** World



3.5 GHz DUAL LINEAR POLARIZATION HIGH-PERFORMANCE 90° SECTOR ANTENNA

The Laird Technologies SA338-90-18-DP 3.5 GHz wideband, dual linear polarized 90° sector antenna, covers the frequency band from 3.3 to 3.8 GHz. Extremely low side lobes, null fill below the horizon and uniform energy distribution within the coverage area are achieved thanks to our highly skilled engineering staff and the utilization of our proprietary Artificial Intelligence RF Optimizing development tool. Laird Technologies' suite of high-performance sector antennas feature proprietary design elements resulting in extremely high levels of system performance and ruggedness while maintaining very slim profiles with low wind and ice loading.

FEATURES <a>Rohs


- Best in class f/b ratio
- Maximum null fill below the horizon
- Extraordinary low side lobe performance
- Rugged tilt mount hardware included
- Robust carrier class construction

PARAMETER	SPECIFICATIONS
Frequency Range	3300-3800 MHz
Bandwidth	500 MHz
Gain	2 x 18 dBi
Horizontal Beamwidth	90°
Vertical Beamwidth	6.5°
F/B Ratio	>21 dB
Isolation	>25 dBm
VSWR	<1.5Typel; Max 1.8
Nominal Impedance	50Ω
Polarization	V and H
Max. Power	100 W
Dimension	700 mm x 140 mm x 50 mm
Weight	5 Kg
Rated Wind Velocity	60 m/s
Connector Type	2 x N-female
Dia. Of Pole	30-70 mm


MARKETS

- Wireless broadband service provider
- Large carrier class deployment
- Optimized for MIMO space time processing
- Outstanding levels of antenna-to-antenna co-located isolation

ANTENNA PATTERNS







global solutions: local support...

Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12 IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022 IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANT-DS-SA3338-90-18-DP 0712

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies maters no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials on yordurs to ran y specific or general uses. Laird Technologies shall not be laible for incidental or consequential damages of any kind. All Laird Technologies reprints and Song specific or general uses. Laird Technologies shall not be laible for incidental or consequential damages of any kind. All Laird Technologies for any kind. All Laird Technologies reprints and conditions of sale in effect from time to time, a cory of which will be furnished upon request. @ Copyright 2012 Laird Technologies, the Laird Technologies to Logy, and other marks can reade marks of registred trademarks of registred trademarks on cory of which will be furnished upon request. @ Copyright 2012 Laird Technologies, the Laird Technologies, the Laird Technologies, the Laird Technologies to Logy, and other marks can reade marks of registred trademarks of registred trad

Optimized to Outstanding co-located is WiMAX