

## Screw connection - WP-GT BRASS M20 - 3241033

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland made from brass with metric thread, rotatable, IP40 protection

The figure shows the WP-GT BRASS M10 version

### Key Commercial Data

Packing unit	1 STK
Minimum order quantity	10 STK
Weight per Piece (excluding packing)	40.0 g
Custom tariff number	74122000
Country of origin	Germany

### Technical data

#### Dimensions

Width (a)	29 mm
Height	35 mm
Wrench size	27.00 mm
Outside diameter	21.00 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 250 °C
Degree of protection	IP40

#### General

Color	Brass
Type	Rotatable
	Outer thread
Components	Halogen-free
Material	Brass

# Screw connection - WP-GT BRASS M20 - 3241033

## Classifications

### eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209
eCl@ss 5.0	21132007
eCl@ss 5.1	21132007
eCl@ss 6.0	21132007
eCl@ss 7.0	27439210
eCl@ss 8.0	27439203

### ETIM

ETIM 3.0	EC000519
ETIM 4.0	EC000519
ETIM 5.0	EC001180

### UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

## Approvals

### Approvals

---

Approvals

VDE Zeichengenehmigung

---

Ex Approvals

---

Approvals submitted

---

### Approval details

VDE Zeichengenehmigung 
--

## Screw connection - WP-GT BRASS M20 - 3241033

### Accessories

#### Accessories

#### Corrugated pipe

Protective hose - WP-STEEL ZC 21 - 3240699



Protective hose in galvanized steel

---

Protective hose - WP-STEEL S 21 - 3240688



Protective hose in stainless steel

---

### Mounting material

Protective hose fixing bracket - WP-BASE A M20 - 3241084



Fixing bracket for protective sleeves, fixed with two screws

---