

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918
Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

## **Scanner Click**





PID: MIKROE-4108

**Scanner Click** as his name said, is an optical scanner expansion board for building optical costsensitive scanners and printers. The main component of this board is a 102 pixels linear optical array sensor marked TSL3301CL from AMS. For accessing sensor registers from any host controller communication is accomplished through a three-wire SPI high speed serial interface. This linear optical sensor provides high density pixel count and integrated analog-to-digital conversion to the Scanner click, and also enables high resolution scanning and scalable operating range. This Click board™ is most suitable for the applications like scanners, printer edge detect and optical character recognition.

Scanner Click is supported by a mikroSDK compliant library, which includes functions that simplify software development. This Click board $^{\text{\tiny M}}$  comes as a fully tested product, ready to be used on a system equipped with the mikroBUS $^{\text{\tiny M}}$  socket.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.



MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

## **Specifications**

Туре	Optical
Applications	Can be used for applications like scanners, printer edge detect and optical character recognition.
On-board modules	Scanner Click uses the TSL3301CL IC, $102 \times 1$ linear optical sensor array with onboard A/D conversion from AMS-AG.
Key Features	High density 102 pixel count and integrated analog-to-digital conversion sensor, with high resolution scanning of 300dpi and scalable operating range
Interface	SPI
ClickID	No
Compatibility	mikroBUS
Click board size	S (28.6 x 25.4 mm)
Input Voltage	3.3V or 5V
Category	Click Boards

## Resources

mikroBUS™

mikroSDK

Click board™ Catalog

Click Boards™

## **Downloads**

Scanner click example on Libstock

Scanner click 2D and 3D files

TSL3301 datasheet

Scanner click schematic

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.