

Technical Data Sheet

USB to RS-232 Serial Adapter w/ LED Indicators Windows 10 Support

Model Number: GM-FTDI2-LED

Rev 03.210315



Newly designed USB to rs232 adapter with full LED serial activity indicators, a new sleek design and modified color scheme give this serial adapter a great look to suit any application. It follows the standard DB9 pinout with hex nut screw lock mechanisms.

Features

- 5ft in length serial adapter. Connect legacy DB-9 serial communications devices to a modern computer with USB
- Easy test RS-232 host to device link. With a full LED, dual color display, tester output
- Supported OS platforms are Windows 7, 8 and 10 as well as Linux and MacOS 10.X
-

Product Information

- Model Number: GM-FTDI2-LED
- Packing List:
 -

Specifications
OVERVIEW

Product Type	Serial Adapter
Electrical Protections	15KV ESD Protection
Mountable	
Material	
Compliance	N/A
LED indicators	All Signals
Requires Host to Function	

0

Serial Modes	RS232
RS232 Signals	DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI
RS422 Signals	
RS485 2-wire Signals	
RS485 4-wire Signals	

SERIAL SPECS

Maximum Data Rate	460.8 Kbps
Minimum Data Rate	300 baud/bps
Data Bits	
Parity	
Stop Bits	
Flow Control	
FIFO	

Specifications Cont.**ENVIRONMENTAL**

Operating Temperature	-40C ~ 85C
Operating Humidity	5% to 95% RH
Storage Temperature	-40C ~ 85C

PHYSICAL

Length	inches
Width	inches
Height	inches
Item Weight	lbs
Ship Weight	0.1870 lbs

OS SUPPORT

Supported Operating Systems	Linux, OSX 10, Windows 10, Windows 8, Windows 7, Windows Vista, Windows XP
-----------------------------	--

WARRANTY

Warranty Period	
-----------------	--

PRODUCT URL

GM-FTDI2-LED Product Page	
---------------------------	--