



NOTE: 1) ALL DIMS. ARE IN MILLIETER OMD
2) BRASS PINS WITH NICKEL PLATED

TEST SPECIFICATION

EACH PLUG IS 100% TEST TO THE FOLLOWING	
EARTH CONTINUITY	
POLARITY	
INSULATION RESISTANCE	500V d.c.
ELECTRICAL STRENGTH	2.0kV, 50Hz

PART NO.	L ±	APPROVED
COLOR	LENGTH TOTAL TOLERANCE: 500 ≥ L ± 20 500 < L < 1000 ± 30 L ≥ 1000 ± 50	

PRODUCT SPECIFICATION
 PLUG NO. SP-023 EUROPEAN TWO-POLE PLUG WITH DUAL EARTHING CONTACTS FOR CLASS I APPLIANCES
 RATING : 16A 250V
 STANDARD: CEE7 NEM-EN50075
 APPROVALS:

MARKING:
 1-SHONG
 16A 250V-095300

 035943

△ JACKET COLOR: BLACK
 MARKING:
 1-SHONG <DCE> KEMA-K00R 405+03+10 <DVE> Δ CEEB2 800
 NF-USE 1105 IEMMEQU H05W-F 30 0.75mm²
 3ASL/75 088226 EG 227

UNLESS OTHERWISE SPECIFIED TOLERANCE	
0.	±1.0
.0	±0.5
.00	±0.3
SCALE: AS SHOWN	UNIT: mm

ASSMANN
 Electronics
 AK535-1.8
 DRAWN NAME:
 PRODUCT NO.
 FILE NAME: B11E0703A0013(N)

REV.	DESCRIPTION	DATE	SIZE	REV.
C	ECN-0505116(Emily) (7,F)(9,E)	05/19/05	A4	C
B	ECN-0505049(Emily) (1,B)	04/27/05		
A	ECN-0504100(Emily)	04/12/05		

DRAWN: JOE 05/19/05
 CHECKED: Pearl 05/20/05
 APPROVED: Joseph 05/20/05