

#### General ordering data

Order No.	0380480000
Part designation	SAK 2.5/35 BL
Version	Feed-through terminal, 2.5 mm <sup>2</sup> , Screw connection, PA 66, blue, TS 35
EAN	4008190131869
Qty.	100 pc(s).

#### Product notes

Note, technical data	With twin ferrules ZH 0.5 to ZH 1.5, rated voltage is 690 V.
----------------------	--

#### PT OKIECEEx/ATEX rating data

EU-type examination certificate	KEMA97ATEX1798U
Download, German	KEMA97ATEX1798U_d.pdf
Download English	KEMA97ATEX1798U_e.pdf
IECEX Certificate of Conformity	IECEXKEM06.0014U
ATEX voltage	550 V
ATEX current	21 A
ATEX conductor cross-section	2 mm <sup>2</sup>
IECEX voltage	550 V
IECEX current	21 A
IECEX conductor cross-section	2.5 mm <sup>2</sup>
Voltage when using cross-connections	CrossConnectionGuide.pdf
Operating temperature range	Einsatztemperaturbereich siehe EG-Baumusterprüfbescheinigung/IECEX-Certificate of Conformity
Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

#### Additional technical data

Colour of insulating material	blue
Connection direction	on side
End plate required	Yes
Explosion-tested version "Ex e"	Yes
Installation advice	TS 35
Insulating material	PA 66
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	right
Operating temperature range	- 50 °C, + 100 °C
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V2
Version	Feed-through terminal

#### CSA rating data

Voltage (CSA)	600 V
CSA current	25 A

#### CSA rating data

Min. cross-section (CSA)	AWG 26
Max. cross-section (CSA)	AWG 10

#### Conductors for clamping (additional connection)

Flexible with ferrule, min. (DIN 46228 pt 1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228 pt 1)	4 mm <sup>2</sup>

#### Conductors for clamping (rated connection)

Clamping range, min.	0.13 mm <sup>2</sup>
Clamping range, max.	6 mm <sup>2</sup>
Type of connection	Screw connection
2nd type of connection	screwed
Connection direction	on side
No. of connections	2
Stripping length	10 mm
Clamping screw	M 2.5
Blade size	0.6 x 3.5 mm
Tightening torque range	0.4...0.6 Nm
Torque level with DMS electric screwdriver	1
Gauge to IEC 60947-1	A3
Solid, min.	0.5 mm <sup>2</sup>
Solid, max.	6 mm <sup>2</sup>
Stranded, min.	0.5 mm <sup>2</sup>
Stranded, max.	4 mm <sup>2</sup>
Flexible, min.	0.5 mm <sup>2</sup>
Flexible, max.	4 mm <sup>2</sup>
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm <sup>2</sup>
Flexible with ferrule, max. (DIN 46228/1)	4 mm <sup>2</sup>
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0.5 mm <sup>2</sup>
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	4 mm <sup>2</sup>
Twin wire-end ferrule, min.	0.5 mm <sup>2</sup>
Twin wire end ferrule, max.	1.5 mm <sup>2</sup>
AWG conductor size, min.	AWG 26
AWG conductor size, max.	5.26 mm <sup>2</sup>

#### Dimensions

Width	6.1 mm
Height of lowest version	40 mm
Length	44.5 mm
TS 35 offset	25 mm

#### Disconnect terminals

Torque level with DMS electric screwdriver	1
--	---

#### Rating data

Rated cross-section	2.5 mm <sup>2</sup>
Rated voltage	800 V
Rated impulse voltage	8 kV

#### Rating data

Rated current	24 A
Standards	IEC 60947-7-1
Current with max. conductor	41 A
Pollution severity	3

#### UL rating data

Voltage (UL)	600 V
Current (UL)	20 A
Min. cross-section (UL)	AWG 22
Max. cross-section (UL)	AWG 12

#### Approvals

Approvals institutes



#### Classifications

ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

#### Similar products

Order No.	Part designation	Version
0499560000	SAK 2.5/10/35	Feed-through terminal, 2.5 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 35
0380460000	SAK 2.5/35	Feed-through terminal, 2.5 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 35
0380440000	SAK 2.5/35 OR	Feed-through terminal, 2.5 mm <sup>2</sup> , Screw connection, PA 66, Orange, TS 35
0268860000	SAKD 2.5/35	Feed-through terminal, 2.5 mm <sup>2</sup> , Screw connection, PA 66, beige, TS 35
0268880000	SAKD 2.5/35 BL	Feed-through terminal, 2.5 mm <sup>2</sup> , Screw connection, PA 66, blue, TS 35