

Recommended PCB Layout  
(Bottom View)

**Materials and Finish**

Housing: PBT Thermoplastic  
15% Glass Filled, UL 94V-0  
Rated, Black Color

Contact Material:  
Pin #1: Copper Alloy, Nickel Plated  
Pin #2 and Pin #5:  
Phosphor Bronze, Matte  
Tin Plated

**Electrical Characteristics**

Insulation Resistance:  
100 Megohms at 500V DC

Contact Resistance:  
50 milliohms Max.

Dielectric Withstanding Voltage:  
500V AC RMS for 1 Minute

**Mechanical Characteristics**


Insertion Force: 0.4kg - 3.0kg

Withdrawal Force: 0.3kg - 3.0kg

Durability: 5000 Mating Cycles Min.

Operating Temperature:  
-25°C to +100°C

**SCHEMATIC**



**Tolerances**

X.X ± 0.35  
X.XX ± 0.25  
Unless Stated  
Otherwise

**RoHS COMPLIANT**



REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A0	5/26/05	New Drawing	H. MA	C. Furumasu	H. MA	5/26/05
A1	6/7/06	Release Drawing	H. MA	N/A		
B1	10/18/10	ECO #10-068	P. DalCanto	H. MA		
B2	5/2/11	ECO #11-027	P. DalCanto	H. MA		
B3	1/6/12	ECO #12-001	P. DalCanto	H. MA		
B4	08/14/18	Update Address	D. Shehan	N/A		

**STX-3200-3NB**

High Profile Stereo Jack, 3 pos., RoHS compliant

Metal Bushing, Nonthreaded, with Backplate

