



**Models 7158 , 7159, 7160**  
**1/4" 2 & 3-Cond. Phone Jack, PC Board Mount**



Model 7158 Horizontal 3-Conductor Jack, PC Board Mount



Model 7159 Horizontal 2-Conductor Jack, PC Board Mount



Model 7160 Horizontal 3-Conductor Jack, Solder Tabs

Use to mount securely with PC boards.

**Features**

- Connects with standard commercial phone plugs
- PC board mountable
- Stereo and mono versions
- Solderable
- 2 and 3 conductor versions

**Materials**

- Shell: Polyamide 6.6 15% GR
- Contacts: Nickel silver

**Ordering Information**

Model: 7158, 7159, 7160

**Specifications**

Number of conductors	2 (Mono)-Model 7159 3 (Stereo)-Models 7158, 7160
Contact resistance	< 15 mΩ
Dielectric strength	1000 V dc
Insulations Resistance	1000 MΩ

**USA:** Sales: 800-490-2361 Technical Support: 800-241-2060 Fax: 888-403-3360

**Europe:** 31-(0) 40 2675 150 **International:** 425-446-5500

e-mail: [technicalsupport@pomonatest.com](mailto:technicalsupport@pomonatest.com)

Where to Buy: [www.pomonaelectronics.com](http://www.pomonaelectronics.com)

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.