



PRODUCT SPECIFICATIONS

LoRaWAN™ Sensor Device

MODEL: LS-111P (CO₂)

Version: V1.2



GlobalSat WorldCom Corporation
16F., No. 186, Jian 1st Rd, Zhonghe Dist.,
New Taipei City 23553, Taiwan
Tel: 886.2.8226.3799/ Fax: 886.2.8226.3899
lora@globalsat.com.tw
www.globalsat.com.tw

USGlobalSat Incorporated
14740 Yorba Court Chino, CA 91710
Tel: 888.323.8720 / Fax: 909.597.8532
sales@usglobalsat.com
www.usglobalsat.com

Introduction:

LS-111P is designed to measure Carbon Dioxide (CO₂), Temperature and Humidity by LoRa[®] long-range and low-power wireless connectivity. It is integrated LoRa[®] wireless technology, CO₂ sensor knowhow and high-performance MCU solution for various IoT markets usage. With calibrated CO₂ sensor module and compensated Temperature/ Humidity sensor integration, the data is ready for use. It is perfect for monitoring air quality in schools, office buildings, greenhouses, factories, hotels, hospitals, transportation lines and anywhere high levels of carbon dioxide are generated.

Product Features:

- LoRaWAN[™] compliant
- High Receiver Sensitivity, Long Range Solution
- Integrated with calibrated CO₂ Sensor
 - Accuracy: ± 50 ppm, $\pm 3\%$ of reading
 - Range: 0 ~ 10,000 ppm
- Integrated with Compensated Temp/ RH Sensor
- Wide range DC power-in, 8~24V /or Micro-USB DC power-in, 5V
- Display CO₂ concentration, Temp/ RH
- Alarm LED indicator

Specifications

Wireless	
LoRa® Module	LoRa Alliance™ certified module LM-130H
Sensitivity	-132 dBm @ 980 bps
Tx Power	Up to 100mW
Standard/ Protocol	Comply with LoRaWAN™ protocol
LoRa® Antenna	External Omni Antenna 824 ~ 960 MHz 2 dBi SMA Male connector
Frequency	863 ~ 870 MHz (EU) 902 ~ 928 MHz (US) 920 ~ 928 MHz (ROA)
Sensor Operation	
Sensing Element	CO ₂ : Gold-plated infrared (NDIR) wave-guide technology with Automatic Baseline Correction (ABC) and passive gas diffusion (no moving parts) Temperature & Humidity: CMOS sensor
Response Time	CO ₂ : < 10 sec. @ 30 cc/min. flow rate < 3 min. diffusion time Temperature: min. 3 sec. ; max. 30sec. at τ 63% Humidity: < 8 sec. at τ 63%
Accuracy (at 25°C)	CO ₂ : ± 50 ppm or ± 3% of reading Temperature: ± 0.5°C Humidity: ± 5 %RH
Repeatability	CO ₂ : ± 20 ppm + (± reading * 1%) Temperature: ± 0.3 °C Humidity: ± 0.3 %RH
Zero Drift	CO ₂ : < ± 10 ppm/yr. with Automatic Baseline Correction (ABC) Temperature: < 0.04 °C/yr Humidity: < 0.5 %RH/yr
Measurement Range*	CO ₂ : 0 ~ 10,000 ppm Temperature: -40 ~ +125 °C Humidity: 0 ~ 85 %RH
Pressure Dependence	CO ₂ : 1.6% reading per kPa
System Operation	
Temperature	-10 ~ +60 °C
Humidity	0 ~ 85 %RH Non-condensed, 0 to 50°C
Storage Temperature	-20 ~ +70 °C.

Specifications

Warm-up Time	≤ 1 min. (at full specs ≤ 15 minutes.)
LED Indicator	Orange LED x 1 (by threshold setting, default is 800 ppm) Red LED x 1 (by threshold setting, default is 1000 ppm)
Power Supply	DC 8 ~ 24 V or Micro-USB DC 5 V
Power Consumption	TBD
Installation	Wall-mount
Dimension (mm)	Wall-mount: 113.57(H) x 80(W) x 28.79(D) mm
Weight	101 ± 2 g
Case Material	ABS
Accessory	
Standard	LoRa [®] Antenna (External Omni Antenna) x 1
Optional	Sensor Programmable Cable (Micro USB to UART)