

MCZ SERIES MCZ R 24VDC 1CO AU TRAK

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



The MCZ R relay couplers, with a width of only 6 mm, are the thinnest in their class.

They are distinguished by the following features:

- Tension clamp connection
- Integrated cross-connection in input/output.
Clampable conductor cross-section is 0.5 to 1.5 mm²

General ordering data

Order No.	8790520000
Type	MCZ R 24VDC 1CO AU TRAK
Version	MCZ SERIES, Relays, No. of contacts: 1, CO contact, AgSnO 5µm Au, Rated control voltage: 24 V DC +25 % / -30 %, Continuous current: 6 A, Tension clamp connection
GTIN (EAN)	4032248479535
Qty.	10 pc(s).

MCZ SERIES

MCZ R 24VDC 1CO AU TRAK

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Ratings

Conductor connection system	Humidity	95 % for 30 days, minimal condensation to EN 50155
Tension clamp connection	Wire cross-section, solid, max.	1.5 mm ²
Open sides	right	

Dimensions and weights

Width	6 mm	Height	91 mm
Depth	63.2 mm	Net weight	27.6 g

Temperatures

Operating temperature	-25 °C...+70 °C	Note: room temperature (service)	+85 °C for 10 minutes
Storage temperature	-40 °C...+85 °C		

Connection data

Clamping range, rated connection	1.5 mm ²	Clamping range, rated connection, min.	0.5 mm ²
Clamping range, rated connection, max.	2.5 mm ²	Stripping length, rated connection	12 mm
Wire connection cross section, finely stranded, max.	1.5 mm ²		

Input

Rated control voltage	24 V DC +25 % / -30 %	Rated current DC	11.5...16.5 mA
Power rating	195...500 mW	Pull-in (sparkover) / drop-out voltage DC coil	14 V / 3 V
Status indicator	Green LED	Max. reset time after voltage interruption	10 ms

Output

Rated switching voltage	250 V AC	Max. switching voltage, AC	250 V
Max. switching voltage, DC making current	250 V / 6 A	Continuous current	6 A
Switch-on delay	< 11 ms	Max. switching power	1500 VA
Min. switching power	1 V / 1 mA	Switch-off delay	< 50 ms
		Max. switching frequency at rated load	0.1 Hz

Contact specifications

No. of contacts	1	Contact design	CO contact
Contact material	AgSnO 5µm Au	Mechanical service life	20 x 10 ⁶ switching cycles

Insulation coordination

Rated voltage	300 V	Clearance and creepage distances for control side - load side	≥ 5.5 mm
Dielectric strength for control side - load side	4 kV _{eff} / 1 s	Dielectric strength to mounting rail	4 kV _{eff} / 1 min.
Impulse withstand voltage	4 kV (1.2/50 µs)	Protection degree	IP 20
Pollution severity	2	Surge voltage category	III

Other technical data

Version	Relay coupler	Status indicator	Green LED
Free-wheel diode	Yes	Reverse polarity protection	Available

Creation date March 6, 2013 11:34:45 PM CET

**MCZ SERIES
MCZ R 24VDC 1CO AU TRAK**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Further details of approvals / standards

Standards DIN EN 50178, DIN EN 50155

Classifications

ETIM 2.0	EC001437	ETIM 3.0	EC001437
UNSPSC	30-21-19-17	eClass 4.1	39-12-15-35
eClass 5.1	27-37-16-01	eClass 6.0	27-37-16-01
eClass 7.0	27-37-16-01		

Approvals

Approvals



Downloads

Declaration of Conformity [K254_03_11.pdf](#)
[3-D model](#)

**MCZ SERIES
MCZ R 24VDC 1CO AU TRAK**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Drawings

Electric symbol

