

**Data sheet | Item number: 261-404**

Test plug module; with locking latches; modular; for 2-conductor terminal blocks; for 261 Series; gray

[www.wago.com/261-404](http://www.wago.com/261-404)



**Data**

**Electrical data**

Subject to changes. Please also observe the further product documentation!

---

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



### Ratings per IEC/EN

Ratings (note)	Maximum test voltage (touch contact): 48 V (test pins are not touch-proof)
Nominal voltage (III/3)	400 V

### Ratings per IEC/EN 2

Ratings (note) 2	Maximum test current (touch contact): 0.5 A Maximum test current: 6 A (if the test pins are securely connected in the clamping units)
------------------	--

### General information

Test voltage	48 V
Test current	0.5 A

### Physical data

Width	6 mm / 0.236 inches
Module width	6 mm / 0.236 inches

### Material Data

Note (material data)	Information on material specifications can be found here
Color	gray
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Weight	2.3 g

### Environmental requirements

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

### Commercial data

Product Group	9 (Std Chassis Mt Blocks)
eCl@ss 10.0	27-14-11-48

Subject to changes. Please also observe the further product documentation!



eCl@ss 9.0	27-14-11-48
ETIM 8.0	EC002555
ETIM 7.0	EC002555
PU (SPU)	100 (25) pcs
Packaging type	box
Country of origin	DE
GTIN	4050821868958
Customs tariff number	85366990990

## Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant, With Exemption
RoHS Exemption	6(c) 7(a) 7(c)-I 7(c)-II
SCIP notification number (Austria)	277569a6-3c62-4aec-8c84-4fea3b95a98a
SCIP notification number (Belgium)	efdf1afd-c9a4-4b52-afff-d02a297a159a
SCIP notification number (Bulgaria)	af199999-a42a-4f9e-847a-016583a6ec7f
SCIP notification number (Czech Republic)	50337d2f-173c-4c86-8829-b7f708954a23
SCIP notification number (Denmark)	ed7d0ee4-53fe-4eb0-a8c1-543eec585f4b
SCIP notification number (Finland)	0fd93198-e575-40cb-b00c-3509f13ac289
SCIP notification number (France)	52c91b9f-6bea-4555-b7a7-b2046c73a39b
SCIP notification number (Germany)	bbf442ee-f8c9-4b37-8168-a3368ab10bb9
SCIP notification number (Hungary)	acf80076-75ec-4bc7-82de-101b5f770197
SCIP notification number (Italy)	a2374a79-a9c7-40e2-96c8-cd50f97c0ca8
SCIP notification number (Netherlands)	926eb167-a5c6-4217-81f3-34d38a3441ae
SCIP notification number (Poland)	364f524c-7bd0-4ede-83eb-8af74da088c9
SCIP notification number (Romania)	ba195b19-5c4f-4cad-be28-21f54f437a87
SCIP notification number (Sweden)	25ed6de5-fa7d-4136-a45f-e68e4bfbbb26

## Optional accessories

### Testing and measuring

Testing accessories	
<b>Item no.: 210-136</b>	<a href="http://www.wago.com/210-136">www.wago.com/210-136</a>
Test plug; 2 mm Ø; with 500 mm cable; red	

Subject to changes. Please also observe the further product documentation!



## Downloads

### Documentation

#### Bid Text

261-404 X81 - Datei	2019 年2月19 日	xml 3.2 kB	Download
------------------------	--------------	---------------	----------

261-404 doc - Datei	2017 年8月18 日	doc 25.1 kB	Download
------------------------	--------------	----------------	----------

#### Additional Information

pdf 2.3 MB	Download
---------------	----------

## CAD/CAE-Data

### CAD data

2D/3D Models 261-404	URL	Download
----------------------	-----	----------

### CAE data

WSCAD Universe 261-404	URL	Download
------------------------	-----	----------

ZUKEN Portal 261-404	URL	Download
----------------------	-----	----------

## Environmental Product Compliance

### Compliance Search

Environmental Product Compliance 261-404 Test plug module; with locking latches; modular; for 2-conductor terminal blocks; for 261 Series; gray	URL	Download
--	-----	----------

## Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



Testing via test plug modules snapped onto a terminal strip – wired or unwired. As touch contact is made with the CAGE CLAMP® (spring steel) unit, this testing type is limited to maximum 0.5 A.

Testing after the conductors have been terminated.

Distance between locking devices must be approximately 35 ... 40 mm!

Subject to changes. Please also observe the further product documentation!