


E160-6U-3 6U X 160MM

Circuit Pattern:
Width/Thick:
Height:
16-Pin DIP Capacity:
Material:
Wire-Wrap Terminals:
Wire-Wrap Socket Pins:
Rec. Card Cage:
96-Pin Din Connector:

Hole Diameter:

Voltage/Ground Plane 6.30"/.062"
 9.19"
 105
 FR4 Epoxy Glass
 T44, T46, T49, T68
 R50, R51, R52, R53
 CCK160-6U
 RE96MWR
 (Available Separately)
 .055"

- Overall voltage and ground planes on opposite board sides provide excellent shielding and power distribution
- To simulate plated-thru holes committed to voltage or ground planes, use Vector T123 eye lets, available separately) for use without pins
- Layout paper and instructions included
- Row and column legends provided




4615 6U X 160MM

Circuit Pattern:
Width/Thick:
Height:
16-Pin DIP Capacity:
Material:
Wire-Wrap Terminals:
Wire-Wrap Socket Pins:
Rec. Card Cage:
96-Pin Din Connector:

Hole Diameter:

3-Hole Solder Pad 6.30"/.062"
 9.19"
 50
 FR4 Epoxy Glass
 T44, T46, T49, T68
 R32
 CCK160-6U
 RE96MWR
 (Available Separately)
 .042"

- 3-hole solder pads (0.28" x 0.080") for interconnecting multiple component leads
- Bus and pad surfaces solder-coated for user convenience
- Interleaved buses on both sides, back-to-back
- Layout paper and instructions included
- Row and column legends provided




E220-6U-1 6U X 220MM

Circuit Pattern:
Width/Thick:
Height:
16-Pin DIP Capacity:
Material:
Wire-Wrap Terminals:
Wire-Wrap Socket Pins:
Rec. Card Cage:
96-Pin Din Connector:

Hole Diameter:

Pad-per-hole 8.66"/0.62"
 9.19"
 140
 FR4 Epoxy Glass
 T44, T46, T49, T68
 R32
 CCK220-6U
 RE96MWR
 (Available Separately)
 .042"

- Plated-thru holes
- Voltage and ground buses around board perimeter both sides
- Pad and Bus surfaces solder-coated for user convenience
- Also accepts PGA 's and PLCC's
- Layout paper and instructions included
- Row and column legends provided



E220-6U-2 6U X 220MM

Circuit Pattern:
Width/Thick:
Height:
16-Pin DIP Capacity:
Material:
Wire-Wrap Terminals:
Wire-Wrap Socket Pins:
Rec. Card Cage:
96-Pin Din Connector:

Hole Diameter:

Peripheral Buses 8.66"/.062"
 9.19"
 140
 FR4 Epoxy Glass
 T44, T46, T49, T68
 R32
 CCK220-6U
 RE96MWR
 (Available Separately)
 .042"

- Voltage and ground buses around board perimeter both sides
- Bus surfaces solder-coated for user convenience
- Also accepts PGA 's and PLCC's
- 58 x 78 grid unrestricted component placement area
- Layout paper and instructions included
- Row and column legends provided

E220-6U-3**6U X 220MM****Circuit Pattern:****Width/Thick:****Height:****16-Pin DIP Capacity:****Material:****Wire-Wrap Terminals:****Wire-Wrap Socket Pins:****Rec. Card Cage:****96-Pin Din Connector:****Hole Diameter:**

Voltage/Ground plane

8.66"/.062"

9.19"

168

FR4 Epoxy Glass

T44, T46, T49, T68

R50, R51, R52, R53


CCK220-6U

RE96MWR

(Available Separately)

.055"

- Overall voltage and ground planes on opposite board sides provide excellent shielding and power distribution
- Plane surfaces solder-coated for user convenience
- To simulate plated-thru holes committed to voltage or ground planes, use Vector T123 eyelets, available separately (for use without pins)
- Layout paper and instructions included

**9U****E280-9U-1****9U X 280MM****Hole Diameter:****Circuit Pattern:****Width/Thick:****Height:****16-Pin DIP Capacity:****Material:****Wire-Wrap Terminals:****Wire-Wrap Socket Pins:****Rec. Card Cage:****96-Pin Din Connector:**

.042"

Pad-Per-Hole

11.02"/.062"

14.44"

270

FR4 Epoxy Glass

T44, T46, T49, T68


R32

CCK280-9U

RE96MWR

(Available Separately)

- Voltage and ground buses around board perimeter both sides
- Accepts PGA and PLCC devices
- Additional power and ground buses in signal area
- Layout paper and instructions included
- Row and column legends provided
- Plated-thru holes

**E280-9U-2****9U X 280MM****Circuit Pattern:****Width/Thick:****Height:****16-Pin DIP Capacity:****Material:****Wire-Wrap Terminals:****Wire-Wrap Socket Pins:****Rec. Card Cage:****96-Pin Din Connector:****Hole Diameter:**

Peripheral Buses

11.02"/.062"

14.44"

270

FR4 Epoxy Glass

T44, T46, T49, T68


R32

CCK280-9U

RE96MWR

.042"

- Voltage and ground buses around board perimeter both sides
- Bus surfaces solder-coated for user convenience
- Capacity for mounting 270, 16-pin DIP IC devices; also accepts PGA and PLCC devices
- Additional power and ground buses in signal area
- Three 79 x 36 grid unrestricted component placement areas
- Layout paper and instructions included
- Row and column legends provided

**E280-9U-3****9U X 280MM****Circuit Pattern:****Width/Thick:****Height:****16-Pin DIP Capacity:****Material:****Wire-Wrap Terminals:****Wire-Wrap Socket Pins:****Rec. Card Cage:****96-Pin Din Connector:****Hole Diameter:**

Voltage/Ground Plane

11.02"/.062"

14.44"

348

FR4 Epoxy Glass

T44, T46, T49, T68

R50, R51, R52, R53

CCK280-9U

RE96MWR

.055"

- Overall voltage and ground planes on opposite board sides provide excellent shielding and power distribution
- Additional power and ground buses in signal area
- To simulate plated-thru holes committed to voltage or ground planes, use Vector T123 eyelets, available separately (for use without pins)
- Layout paper and instructions included
- Row and column legends provided

