


Accessories - FL 3-H - 1760310

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


PCB terminal block, pitch: 2.5 mm, number of positions: 3, connection method: Slip-on connection, mounting: Wave soldering, color: green

Why buy this product

- ✓ Space-saving, standardized slip-on connection allows worldwide use
- ✓ Two solder pins reduce the mechanical strain on the soldering spots
- ✓ The latching on the side enables various numbers of positions to be combined
- ✓ Well-known mounting principle allows worldwide use



Key Commercial Data

Packing unit	1
GTIN	 4 017918 030858
GTIN	4017918030858
Custom tariff number	85369010

Technical data

Dimensions

Pitch	2.5 mm
Constructional height	13.3 mm
Height [h]	18.3 mm
Pin dimensions	0,8 x 1,0 mm
Pin spacing	5.00 mm
Hole diameter	1.3 mm

General

Range of articles	FL
Nominal cross section	0 mm ²
Insulating material	PA 6.6
Solder pin surface	Sn
Flammability rating according to UL 94	V2

Accessories - FL 3-H - 1760310

Technical data

General

Number of positions	3
---------------------	---

Standards and Regulations

Connection in acc. with standard	CSA
Flammability rating according to UL 94	V2

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440490
eCl@ss 8.0	27440402
eCl@ss 9.0	27440402

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002498
ETIM 5.0	EC002637
ETIM 6.0	EC002637

UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Accessories - FL 3-H - 1760310

Approvals

Approvals

CSA / EAC / cULus Recognized

Ex Approvals

Approval details

CSA		http://www.csagroup.org/services/testing-and-certification/certified-product-listing/	13631
Nominal current I _N		10 A	
Nominal voltage U _N		300 V	

EAC			B.01742
-----	--	--	---------

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E60425-19770427
Nominal current I _N		10 A	
Nominal voltage U _N		300 V	

Accessories

Accessories

Insulating sleeve

Insulating sleeve - PT/FS 6,3 - 0604707



Insulating sleeve, as touch protection, slide onto the conductor before for 6.3 slip-on sleeves

Labeled terminal marker

Accessories - FL 3-H - 1760310

Accessories

Marker pin Zack strip - BNB-ZB 5,LGS:FORTL.ZAHLEN - 1400201



Marker pin Zack strip, Strip, white, labeled, Printed horizontally: Consecutive numbers 1 - 10, 11 - 20, etc. up to 491 - 500, Mounting type: Plug in, for terminal block width: 5 mm, Lettering field: 4 x 4 mm

Marker pen

Marker pen - B-STIFT - 1051993



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

Terminal marking

Marker pin Zack strip - BN-ZB 5/WH:UNBEDRUCKT - 1400078



Marker pin Zack strip, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, Mounting type: Plug in, for terminal block width: 5 mm, Lettering field: 4 x 4 mm