

#### **CHAMP**

TE Internal #: 6339447-7

PCB D-Sub Connectors, Receptacle, Cable-to-Board, 50 Position, 2.16 mm [.085 in] Centerline, 2 Row, Standard Profile, Right Angle,

PCB Mount Retention

View on TE.com >



Connectors > D-Shaped Connectors > D-Sub Connectors > PCB D-Sub Connectors > D-Sub Shielded Receptacle Assembly: Right Angle, 2.16mm











Connector & Housing Type: Receptacle

Connector System: Cable-to-Board

Number of Positions: 50

Centerline (Pitch): 2.16 mm [ .085 in ]

Number of Rows: 2

All D-Sub Shielded Receptacle Assembly: Right Angle, 2.16mm (20)

### **Features**

#### **Product Type Features**

Shield Plating Finish

Shield Material

Shield Plating Material

Connector & Housing Type	Receptacle
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	50
Number of Rows	2
PCB Mount Orientation	Right Angle
Body Features	
Assembly Process Feature Material	Carbon Steel

Bright

Nickel

Copper-Zinc Alloy



Campactar Drafile	Ctorodorol
Connector Profile	Standard
Contact Features	
	30 μin
Contact Mating Area Plating Material	Gold
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	3.5 A
Termination Features	
Rectangular Termination Post & Tail Thickness	.25 mm[.01 in]
Rectangular Termination Post & Tail Width	.5 mm[.019 in]
Termination Post & Tail Length	2.29 mm[.09 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Assembly Process Feature Plating Material	Tin
PCB Mount Retention	With
PCB Mount Retention Type	Boardlock
Mating Retention	With
Mating Retention Type	4-40 Tapped Holes
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Polyester GF
Centerline (Pitch)	2.16 mm[.085 in]
Dimensions	
Panel Thickness (Recommended)	1.57 mm[.062 in]
	.062 in
Row-to-Row Spacing	4.3 mm[.169 in]
Usage Conditions	
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
Operation/Application	
Shielded	Yes
Circuit Application	Signal
Packaging Features	



Packaging Quantity	40
Packaging Method	Package

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts



# Customers Also Bought





TE Part #1-406541-1 MJ,INV,1X1,6PNL G,.100"ST,SN



TE Part #1857989-1 Z-PACK/A F-HDR.110P EON



TE Part #1-1932680-1 VLP DDR3 DIMM 240POS. 1.0PITCH





TE Part #2016732-1 RF CA,MCX-RA PLUG TO PLUG,WITH RG316 TE Part #2159942-1 CA POWER CORDE TE Part #2349422-3 Load plate assembly for Cisco HW



TE Part #6-1775855-4
RJ45 OVER USB W/ LED G/Y 50u" Au

### **Documents**

**Product Drawings** 

RCPT ASSY,LP,SHLD,RA50,STD

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_6339447-7\_B.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_6339447-7\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_6339447-7\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications** 

PCB D-Sub Connectors, Receptacle, Cable-to-Board, 50 Position, 2.16 mm [.085 in] Centerline, 2 Row, Standard Profile, Right Angle, PCB Mount Retention



## **Application Specification**

English

Product Environmental Compliance

TE Material Declaration

English

Agency Approvals

UL

English