



NOTES: Finish (Plating Thickness in Micro-inches)
 1. Brass
 2. Thin Gold over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min, Thick
 3. Beryllium Copper
 4. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
 5. Teflon

RoHS Compliant

9	Cover	Note 1	Note 2	1	
8	Contact Pin	Note 1	Note 4	1	
7	Insulator	Note 5	Natural	2	
6	Contact Pin	Note 3	Note 4	1	
5	Insulator	Note 5	Natural	1	
4	Retainer Ring	SUS 303	Natural	1	
3	Gasket	Silicone	Red	1	
2	Shell	Note 1	Note 2	1	
1	Housing with Body	Note 1	Note 2	1	

Dimensions are in Inches
 Unless Otherwise Specified
 Tolerances
 0.5-6 = ±0.2
 6-30 = ±0.4
 30-120 = ±0.6
 120-315 = ±1
 315-1000 = ±1.6
 1000-2000 = ±2.4

Part No.	
Approved	Date 1-15-2015
Checked	Date 1-15-2015
Drawn	Date 1-15-2015

NTE Electronics	
Title	SMA "T" Adapter Jack-Plug-Jack
Drawing No.	06-S010
File No.	