


Material

Terminal body(Contact pin): Brass
 Wire guard: Stainless steel
 Surface of solder tail: Tin plated
 Insulator(housing): Thermoplastic (UL94V-0), GREEN(RAL6018/T1)

Electrical

cULus/VDE
 Voltage rating: 300VAC/450VAC
 Current rating: 10A/10A
 Wire range: 0.75-1.5mm²
 Solid wire(AWG): 14-24
 Stranded wire(AWG): 14-24
 Pull force:
 Screw:

Wire strip length: 9-10mm
 Withstanding Voltage: 1.6KV/2.5KV
 Operating temperature: -40°C to +115°C
 Soldering temperature: 250°C ± 10°C/5 Sec
 Safety Approval:



DIMENSION

P	(N-1)x10.0
---	------------

N=Number of poles

Poles	Tolerance
2p-6p	±0.10
7p-12p	±0.20
13p-18p	±0.25
19p-24p	±0.30

RoHS compliant
 Unit: mm

 File No.: E3349947

Scale	Free TOLERANCE
X.	±0.50
X.X	±0.30
X.XX	±0.10
DIM	TOL
X.°	±1°
Angle	TOL

Date	Name
19.04.2010	Alex
16.04.2013	Amy
14.03.2016	Amy

Customer-No.	ASSMANN WSW-No.	Drawing-No.
		A-TB100-HAXXH
Replace	ASS 4128 CO	rev02
		Sheet



1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	H