2 METERS LENGTH



Connector A 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B FA1-NZSJ-C01-0 FAKRA Jack Straight Brass Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

	Connector A			Cable			Connector B		
	Part #:	132245		Part #:	RG-174	Part #:	FA1-NZSJ-C01-0		
	Description:	SMA R/A BHD Jł	K RG174 RG316 LMR100	Description:	RG-174 - PE 0.1	Description:	FAKRA-Z JK RG174	1 RG316 500	
	Description.	500		Dielectric:	PE	Type:	FAKRA		
	Туре:	SMA		Shielding:	Braid	Gender:	Jack		
	Gender:	Jack		Diameter:	0.1	Body Type:	Straight		
	Body Type:	Right Angle		Impedance: 50 Ohm		Contact Type:	Crimp		
	Contact Type:	Solder		Sheathing:	None	Polarity:	Standard		
	Polarity:	Standard		Testing:	,			50 Ohm	
	Impedance:	50 Ohm		Length:	2 Meters	Mounting:	Cable		
	Mounting:	Bulkhead - Rear	Mount	Longtin	2 Motoro	Body Material:	Brass Nickel		
1	Body Material:	Brass				Body Finish:			
	Body Finish:	Gold				IP Rating:	None		
	IP Rating:	None				Contact Material:	Beryllium Copper		
	Contact Material:	Beryllium Copper Gold 12.4 GHz				Contact Material.	Gold		
	Contact Finish:					Max. Freq.:	3 GHz FAKRA-Z Jack Straight		
	Max. Freq.:								
	Booting: SMA Jack Right Ang		adle			Booting:			
	Dooting.	Civil Y buok Pright /	ingic			Clocking:	0°		
	Amphenol USTOM CABLE			AND MUST NOT BE U TAL TO CUSTOM CA CED OR TRANSCRIB	IUST NOT BE USED D CUSTOM CABLE R TRANSCRIBED			UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY:	
CONTROLLED DOCUMENT DO NOT CODY CUSTOM CABLE INC. ACCEP			NCE OF THIS DRAW			CENTER LABEL IF LENGTH			
CONTROLLED DOCUMENT - DO NOT COLT			ESTABLISHES AND AGREEMENT OF THE FOREGOING.		^{vG.} Q-2P05E0003002N	Q-2P05E0003002M		IS LESS THAN 12 INCHES	