

HDC MHP 200 PE MAS**Weidmüller Interface GmbH & Co. KG**Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

**Flexible**

The four module sizes make for individual plug solutions that save a huge amount of space. The smaller pitch translates into an optimised design too.

General ordering data

Version	Power module
Order No.	2748260000
Type	HDC MHP 200 PE MAS
GTIN (EAN)	4050118890891
Qty.	2 pc(s).

HDC MHP 200 PE MAS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	34 mm	Depth (inches)	1.339 inch
Height	54.6 mm	Height (inches)	2.15 inch
Width	29.2 mm	Width (inches)	1.15 inch
Net weight	89.5 g		

Temperatures

Limit temperature	-40 °C ... 125 °C
-------------------	-------------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1	SCIP	fa505316-3e43-4ad0-930c-360dfdbe
------------	----------------	------	----------------------------------

General data

Material	Polycarbonate	Number of poles	1
Plugging cycles	≥ 500	Pollution severity	3
Required plug-in slots	2	Type	Male
UL 94 flammability rating	V-0		

Version

Conductor cross-section, max.	70 mm ²	Conductor cross-section, min.	25 mm ²
Stripping length, rated connection	16 mm	Type of connection	Axial screw connection

Classifications

ETIM 6.0	EC002312	ETIM 7.0	EC002312
ETIM 8.0	EC002312	ECLASS 9.0	27-44-02-92
ECLASS 9.1	27-44-02-18	ECLASS 10.0	27-44-02-92
ECLASS 11.0	27-44-02-92	ECLASS 12.0	27-44-02-92

Approvals

ROHS	Conform
------	---------

Downloads

Approval/Certificate/Document of Conformity	Manufacturer's declaration
Engineering Data	CAD data – STEP
User Documentation	Manual Axial Screw
Catalogues	Catalogues in PDF-format

HDC MHP 200 PE MAS

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

Drawings

www.weidmueller.com

