

Technical specification:

Rated voltage: 3pos 4pos
IEC 61076-2-104 60 V 30 V

Current rating: 3 A bei 40°C
IEC 61076-2-104

Insulation resistance: >=100 MΩ
IEC 60512

Pollution degree: 3/2
IEC 60664-1

Degree of protection: IP 67, in mated condition
IEC 60529

Temperature range: -30°C ... +85°C
IEC 60664-1

Mating cycles: >=100
IEC 60512-9a

Materials:

Contact: CuZn

Contact plating: Nickel, gold plated


Contact carrier: PA , UL 94

Socket housing: CuZn, Nickel plated

Part no:	Description:	Pos
42-01016	SAL - 8 - ESVM3 - P	3
42-01017	SAL - 8 - ESVM4 - P	4

DO NOT ALTER CAD DRAWING BY HAND
Directive 2002/95/EC RoHS compliant

Index: a 02.03.11 fro Ä3914
Data sheet revised



	date	name
drawn	15.10.08	Fromm
appd.	15.10.08	Mankopf

title:
Male socket M8x1 with dip solder

dwg no:
42K1A116

part no:

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
OWNERSHIP AND COPYRIGHT OF CONEC GmbH

