


In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				STORAGE TEMPERATURE RANGE		-40 °C TO 105 °C	
RATING	OPERATING TEMPERATURE RANGE	-40 °C TO 105 °C (NOTE1)		TEMPERATURE RANGE		-40 °C TO 105 °C	
	VOLTAGE	250 V AC		CURRENT		1 A	
SPECIFICATIONS							
ITEM	TEST METHOD	REQUIREMENTS		QT	AT		
CONSTRUCTION							
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.		X	X		
MARKING	CONFIRMED VISUALLY.			X	X		
ELECTRIC CHARACTERISTICS							
CONTACT RESISTANCE	1A DC.	SIGNAL:30 mΩ MAX, SHIELD:60m Ω MAX.		X	-		
CONTACT RESISTANCE	20 mV AC MAX, 0.1 mA(DC OR 1000Hz)	SIGNAL:30 mΩ MAX, SHIELD:60m Ω MAX.		X	-		
MILLIVOLT LEVEL METHOD							
INSULATION RESISTANCE	500 V DC	100 MΩ MIN.		X	-		
VOLTAGE PROOF	650 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.		X	-		
MECHANICAL CHARACTERISTICS							
CONTACT INSERTION AND EXTRACTION FORCES	BY STEEL GAUGE, -.	INSERTION FORCE - N MAX. EXTRACTION FORCE - N MIN.		-	-		
MECHANICAL OPERATION	30 TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE SIGNAL:30 mΩMAX, SHIELD:60m ΩMAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-		
VIBRATION	FREQUENCY 20 TO 200 Hz, 43.1 ms ² AT 3 h FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② CONTACT RESISTANCE SIGNAL:60 mΩMAX, SHIELD:120m ΩMAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-		
SHOCK	FREQUENCY 20 TO 50 Hz, 66.6 ms ² AT 1 h.	① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② CONTACT RESISTANCE SIGNAL:60 mΩMAX, SHIELD:120m ΩMAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-		
LOCK STRENGTH	APPLYING A PULL FORCE THE MATING AXIALLY AT 98N MAX.	① DURING APPLYING, MATING COMPLETELY. ② AFTER APPLYING,NO DEFECT OF MATING PARTS.		X	-		
ENVIRONMENTAL CHARACTERISTICS							
DAMP HEAT (STEADY STATE)	EXPOSED AT 60 °C, 90 ~ 95 %, 500 h.	① CONTACT RESISTANCE SIGNAL:60 mΩMAX, SHIELD:120m ΩMAX. ② INSULATION RESISTANCE:100 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-		
RAPID CHANGE OF TEMPERATURE	TEMPERATURE:40→5 TO 35→85→5 TO 35°C TIME 30 → 5 → 30 → 5 min UNDER 1000 CYCLES.	① CONTACT RESISTANCE SIGNAL:60 mΩMAX, SHIELD:120m ΩMAX. ② INSULATION RESISTANCE:100 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-		
DRY HEAT	EXPOSED AT 105°C, 300 h.	① CONTACT RESISTANCE SIGNAL:60 mΩMAX, SHIELD:120m ΩMAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-		
COLD	EXPOSED AT -40°C, 120 h.	① CONTACT RESISTANCE SIGNAL:60 mΩMAX, SHIELD:120m ΩMAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-		
RESISTANCE TO SO ₂ GAS	EXPOSED IN 500 PPM FOR 8h.	① CONTACT RESISTANCE SIGNAL:60 mΩMAX, SHIELD:120m ΩMAX. ② NO HEAVY CORROSION.		X	-		
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE			
REMARK (NOTE1) INCLUDE THE TEMPERATURE RISING BY CURRENT.	APPROVED		NH. NAKATA	14.03.03			
	CHECKED		TS. KUBOTA	14.03.03			
	DESIGNED		MH. SHOUJI	14.03.03			
	DRAWN		MH. SHOUJI	14.03.03			
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-169329-00				
HRS		SPECIFICATION SHEET		PART NO.	GT17HNR-4DS-5CF		
		HIROSE ELECTRIC CO., LTD.		CODE NO.	CL767-0292-3-00		
						1/1	