
PSG.2B.308.CLAD42Z PUSH-PULL PLUG, 8 PIN CONTACTS, SOLDER, 4.2 MM COLLET, STRAIN RELIEF NUT



 CONTACT INFO
 DIA

 MALE
 FEMALE
 DIA

 Image: Contact info
 Image: Contact info
 Image: Contact info

 Image: Contact info
 Image: Contact info
 Image: Contact info

 Image: Contact info
 Image: Contact info
 Image: Contact info

 Image: Contact info
 Image: Contact info
 Image: Contact info

 Image: Contact info
 Image: Contact info
 Image: Contact info

 Image: Contact info
 Image: Contact info
 Image: Contact info

 Image: Contact info
 Image: Contact info
 Image: Contact info

 Image: Contact info
 Image: Contact info
 Image: Contact info

 Image: Contact info
 Image: Contact info
 Image: Contact info

 Image: Contact info
 Image: Contact info
 Image: Contact info

 Image: Contact info
 Image: Contact info
 Image: Contact info

 Image: Contact info
 Image: Contact info
 Image: Contact info

 Image: Contact info
 Image: Contact info
 Image: Contact info

 Image: Contact info
 Image: Contact info
 Image: Contact info

 Image: Contact info
 Image: Contact info
 Image: Contact info

 Image: Contact info
 Image: Contact info
 Image: Contact info

 Image: Contact info
 Image: Contact info



KEY SPECIFICATIONS	
CONNECTOR SERIES	PSG
CONNECTOR SIZE	2В
CONNECTOR GENDER	MALE
CODING	G
LOCKING STYLE	SELF LOCKING
ATTACHMENT METHOD	SOLDER
IP RATING	IP 50
COLLET SIZE	4.2 MM
STANDARD MATE SERIES	FSG

GENERAL SPECIFICATIONS	
TEMPERATURE RANGE	-55 DEG C - +200 DEG C
INSULATOR MATERIAL	PEEK
SOLDER CONTACT MATERIAL	COPPER ALLOY, GOLD PLATED
CONNECTOR BODY MATERIAL	BRASS, NICKEL PLATED
COUPLING NUT, SCREW	BRASS, CHROME PLATED
INSULATION RESISTANCE	EQUAL OR GREATER THAN 100 M-OHMS

MILSPECWEST - The Very Best in Micro Interconnect Products AEROSPACE * MEDICAL * AUTOMOTIVE * INDUSTRIAL * MICRO-ELECTRONICS milspecwest.com sales@milspecwest.com 949-636-9677