

## Han 3M RJ45 Hybrid Cat.6A PFT 8+4p



Image is for illustration purposes only. Please refer to product description.

Part number	09 45 215 1761
Specification	Han 3M RJ45 Hybrid Cat.6A PFT 8+4p
HARTING eCatalogue	<a href="https://b2b.harting.com/09452151761">https://b2b.harting.com/09452151761</a>

### Identification

Category	Connectors
Series	RJ45 Hybrid
Element	Panel feed through
Specification	Straight

### Version

Size	Han <sup>®</sup> 3 A
Shielding	Fully shielded, 360° shielding contact
Number of contacts	12
Number of data contacts	8
Number of power contacts	4

### Technical characteristics

Conductor cross-section	1.5 mm <sup>2</sup> Power
Conductor cross-section	AWG 12 Power
Rated voltage (Data)	50 V AC 60 V DC
Rated voltage (power)	48 V DC
Rated current (data)	1.76 A
Rated current (power)	16 A
Transmission characteristics	Cat. 6 <sub>A</sub> Class E <sub>A</sub> up to 500 MHz



Pushing Performance  
Since 1945

## Technical characteristics

Data rate	10 Mbit/s
	100 Mbit/s
	1 Gbit/s
	2.5 Gbit/s
	5 Gbit/s
Limiting temperature	-40 ... +70 °C
Mating cycles	≥500

## Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	Black
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Antimony trioxide
	Lead
	Nickel
	Naphthalene

## Specifications and approvals

UL / CSA	UL 1977 ECBT2.E102079
	CSA-C22.2 No. 182.3 ECBT8.E102079
Approvals	DNV GL
PROFINET	Yes

## Commercial data

Packaging size	1
Net weight	79.5 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140059740



**Pushing Performance**  
Since 1945

## Commercial data

eCl@ss

27440113 Rectangular connectors (set)

---