72 INCHES LENGTH



Connector A 132260 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-142 Continuity/Hi-Pot Connector B 142203 SMB Plug Right Angle Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Connector B	Connector A			Cable			Connector B		
135° 45° 180° 225° 270° 220° 315° Connector A	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	Gold None al: Beryllium Copper		Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-142 RG-142 - ST 0.195 ST Braid 0.195 50 Ohm None Continuity Hi-Pot 72 Inches	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	142203 SMB PLUG RG55 RG142 RG223 500 SMB Plug Right Angle Solder Standard 50 Ohm Cable Brass Gold None Beryllium Copper Gold 4 GHz SMB Plug Right Angle 0°		
THIS DRAWING MAY CONTA PROPRIETARY INFORMATIO FOR ANY PURPOSE DETRIMINIC. IT MAY NOT BE REPROI IN ANY FORM WITHOUT THI CONTROLLED DOCUMENT - DO NOT COPY			AND MUST NOT BE USED TAL TO CUSTOM CABLE CED OR TRANSCRIBED RITTEN CONSENT OF NCE OF THIS DRAWING Part No: Part No:		RA-PL G142 72I	'L G142 72I			