

PCB terminal block - PTSA 1,5/ 2-3,5-Z GY - 1994513

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB terminal block, Nominal current: 2 A, Nom. voltage: 250 V, Pitch: 3.5 mm, Number of positions: 2, Connection method: Spring-cage connection, Mounting: Soldering, Conductor/PCB connection direction: 45 °, Color: Gray

Key commercial data

| | |
|--------------------------------------|----------|
| Packing unit | 1 pc |
| Minimum order quantity | 250 pc |
| Weight per Piece (excluding packing) | 1.12 GRM |
| Custom tariff number | 85369010 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|----------------|---------------|
| Length | 12 mm |
| Height | 13.1 mm |
| Pitch | 3.5 mm |
| Dimension a | 3.5 mm |
| Pin dimensions | 0,4 x 0,75 mm |
| Pin spacing | 3.5 mm |
| Hole diameter | 1 mm |

General

| | |
|----------------------------------|---------------------|
| Range of articles | PTSA 1,5 |
| Rated surge voltage (III/3) | 2.5 kV |
| Rated surge voltage (III/2) | 2.5 kV |
| Rated surge voltage (II/2) | 2.5 kV |
| Rated voltage (III/3) | 200 V |
| Rated voltage (III/2) | 250 V |
| Rated voltage (II/2) | 400 V |
| Connection in acc. with standard | EN-VDE |
| Nominal current I_N | 2 A |
| Nominal cross section | 1.5 mm ² |
| Solder pin surface | Sn |
| Stripping length | 9 mm |
| Number of positions | 2 |

PCB terminal block - PTSA 1,5/ 2-3,5-Z GY - 1994513

Technical data

Connection data

| | |
|--|----|
| Conductor cross section AWG/kcmil min. | 20 |
| Conductor cross section AWG/kcmil max | 16 |
| Minimum AWG according to UL/CUL | 24 |
| Maximum AWG according to UL/CUL | 16 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27141109 |
| eCl@ss 5.0 | 27141190 |
| eCl@ss 5.1 | 27141190 |
| eCl@ss 6.0 | 27261101 |
| eCl@ss 7.0 | 27440401 |
| eCl@ss 8.0 | 27440401 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002643 |
| ETIM 5.0 | EC002643 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211801 |
| UNSPSC 7.0901 | 39121432 |
| UNSPSC 11 | 34131203 |
| UNSPSC 12.01 | 39121432 |
| UNSPSC 13.2 | 39121432 |

Approvals

Approvals

Approvals

UL Recognized / VDE Gutachten mit Fertigungsüberwachung / cUL Recognized / CCA / GOST / GOST / cULus Recognized


Ex Approvals


PCB terminal block - PTSA 1,5/ 2-3,5-Z GY - 1994513


Approvals

Approvals submitted

Approval details

| | | |
|---|-------|-------|
| UL Recognized  | | |
| | B | D |
| mm ² /AWG/kcmil | 24-16 | 24-16 |
| Nominal current I _N | 5 A | 5 A |
| Nominal voltage U _N | 300 V | 300 V |

| | |
|---|----------|
| VDE Gutachten mit Fertigungsüberwachung  | |
| mm ² /AWG/kcmil | 0.5-0.75 |
| Nominal current I _N | 2 A |
| Nominal voltage U _N | 250 V |

| | | |
|--|-------|-------|
| cUL Recognized  | | |
| | B | D |
| mm ² /AWG/kcmil | 24-16 | 24-16 |
| Nominal current I _N | 5 A | 5 A |
| Nominal voltage U _N | 300 V | 300 V |

| | |
|--------------------------------|------|
| CCA | |
| mm ² /AWG/kcmil | 0.75 |
| Nominal current I _N | 2 A |

| | |
|--|--|
| GOST  | |
|--|--|

PCB terminal block - PTSA 1,5/ 2-3,5-Z GY - 1994513

Approvals

GOST 

cULus Recognized 