


28232.7 PVC-VRT-AH 25X50 WH



Device and installation marker, Length: 50 mm, Width: 25 mm, Colour: White

RAL: 9010

Business data

Article number	<u>28232.7</u>
Article name	PVC-VRT-AH 25X50 WH
GTIN (EAN)	4044211214647
Packaging unit	80
Quantity unit	PC
Number of markers per card	8 ST
Weight per piece (not including packaging)	2.3 g
Weight per piece (including packaging)	2.3 g
Unit of weight	G
Customs number	39204910
Country of origin	IT
Prio-Article	28232.7
Product description	Device and installation marker

28232.7 PVC-VRT-AH 25X50 WH

Technical data

Dimensions

Length	50 mm
Width	25 mm
Diameter of mounting hole	4 mm
Thickness	0.9 mm

Materials

Marker material	PVC
Flammability class UL 94	V-0
Working temperature, min.	-30 °C
Working temperature, max.	60 °C
Processing temperature, min.	10 °C
Processing temperature, max.	40 °C
Silicone-free	✓

Further technical data

Mounting	Self-adhesive
Software code	860

Environmental Product Compliance

REACH Candidate Substance Note	No
--------------------------------	----

Media

28232.7 PVC-VRT-AH 25X50 WH

Accessories

Printer



Thermal transfer printer TTPCard including a power cord, USB cable, dust cover, black thermal transfer film (28010.4), three inlays: CCI-PC-SB 5x5 (28020.0), CCI-PC-CPM-10/BSTR (28027.0), CCI-PC/PVC/PVCF (28041.0), CONTASign PRO software in 16 languages (German, English, French, Italian, Dutch, Spanish, Portuguese, Czech, Polish, Bulgarian, Romanian, Slovenian, Turkish, Chinese, Japanese, Russian) for Windows versions 7, 8, 10. (available for download)

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28000.0</u>	TTPCard Set	4044211207397	1 ST

Inlays

Printer inlay

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28041.0</u>	CCI-PC/PVC/PVCF	4044211208097	1 ST