



10 dB Fixed Attenuator, N Male to N Female
 Directional Black Anodized Aluminum Heatsink
 Body Rated to 150 Watts Up to 8 GHz

RF Fixed Attenuators Technical Data Sheet

PE7AP150-10

Features

- Directional
- DC to 8 GHz Frequency Range
- Attenuation 10±1.5 dB
- Max Power 150 Watts (CW)
- VSWR < 1.5:1

Applications

- Instrumentation
- Precision measurements
- Prototyping and characterization
- Production systems

Description

Pasternack carries a wide range of fixed attenuators with a broad selection of attenuation levels, frequency ranges, and power dissipation ranges. RF microwave attenuators (also known as RF pads) lower the amplitude of a signal (attenuate) a known amount and can be used in a wide variety of applications. These attenuator pads are used when a signal needs to be reduced to protect measurement equipment or other circuitry, to extend the range of power meters and amplifiers, and to impedance match circuits by reducing the VSWR seen by adjacent components. RF attenuators can prevent signal overload in amplifiers, receivers and detectors, adjusting the signal level to a range that is optimal.

Few RF components are as commonly used as fixed coaxial attenuators, and Pasternack carries one of the largest in-stock varieties and ships them same day. The 10 dB Fixed Attenuator PE7AP150-10 is rated to 150 Watts and operates from DC to 8 GHz. The versatile coaxial package uses type N male to type N female connectors and is also REACH and RoHS compliant. The Black Anodized Aluminum Heatsink body allows for efficient heat dissipation under high power usage conditions.

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|--|---------|---------|---------|--------|
| Frequency Range | DC | | 8 | GHz |
| Impedance | | 50 | | Ohms |
| Nominal Attenuation | | 10 | | dB |
| VSWR | | | 1.5:1 | |
| Input Power, CW derated linearly to 15W at +125°C | | | 150 | Watts |
| Input Power, Peak 5µs pulse, 0.1% duty cycle | | | 2.5 | kWatts |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [10 dB Fixed Attenuator, N Male to N Female Directional Black Anodized Aluminum Heatsink Body Rated to 150 Watts Up to 8 GHz PE7AP150-10](#)



10 dB Fixed Attenuator, N Male to N Female
 Directional Black Anodized Aluminum Heatsink
 Body Rated to 150 Watts Up to 8 GHz

RF Fixed Attenuators Technical Data Sheet

PE7AP150-10

Specifications by Frequency

| Description | F1 | F2 | F3 | F4 | F5 | Units |
|---------------------------|---------|--------|--------|--------|----|-------|
| Range | DC to 2 | 2 to 4 | 4 to 6 | 6 to 8 | | GHz |
| VSWR, Max | 1.2:1 | 1.3:1 | 1.4:1 | 1.5:1 | | |
| Attenuation Accuracy, Typ | 0.75 | 0.75 | 1.25 | 1.5 | | dB |

Mechanical Specifications

Size

| | |
|---------------------------|----------------------------------|
| Length | 6.39 in [162.31 mm] |
| Width/Diameter | 5.8 in [147.32 mm] |
| Height | 4.21 in [106.93 mm] |
| Weight | 4.583 lbs [2.08 Kg] |
| Body Material and Plating | Black Anodized Aluminum Heatsink |

Configuration

| | |
|---------------|----------------------|
| Design | Fixed, Directional |
| Package Style | Connectorized Module |

Connectors

| Description | Connector 1 | Connector 2 |
|------------------------------|--------------------------|--------------------------|
| Type | N Male | N Female |
| Connector Specification | MIL-STD-348 | MIL-STD-348 |
| Contact Material and Plating | Beryllium Copper, Silver | Beryllium Copper, Silver |
| Body Material and Plating | Stainless Steel, Silver | Stainless Steel, Silver |

Mechanical Specification Notes:

Connector interface in accordance with MIL-STD-348 and MIL-PRF-39012

Environmental Specifications

Temperature

| | |
|-----------------|-------------------|
| Operating Range | -55 to +125 deg C |
|-----------------|-------------------|

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [10 dB Fixed Attenuator, N Male to N Female Directional Black Anodized Aluminum Heatsink Body Rated to 150 Watts Up to 8 GHz PE7AP150-10](#)



10 dB Fixed Attenuator, N Male to N Female
Directional Black Anodized Aluminum Heatsink
Body Rated to 150 Watts Up to 8 GHz

RF Fixed Attenuators Technical Data Sheet

PE7AP150-10




10 dB Fixed Attenuator, N Male to N Female Directional Black Anodized Aluminum Heatsink Body Rated to 150 Watts Up to 8 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [10 dB Fixed Attenuator, N Male to N Female Directional Black Anodized Aluminum Heatsink Body Rated to 150 Watts Up to 8 GHz PE7AP150-10](https://www.pasternack.com/10db-fixed-n-male-n-female-150-watts-attenuator-pe7ap150-10-p.aspx)

URL: <https://www.pasternack.com/10db-fixed-n-male-n-female-150-watts-attenuator-pe7ap150-10-p.aspx>


PE7AP150-10 CAD Drawing

10 dB Fixed Attenuator, N Male to N Female Directional Black Anodized Aluminum Heatsink Body Rated to 150 Watts Up to 8 GHz



| STANDARD TOLERANCES | |
|---------------------|--------|
| .X | ±0.2 |
| .XX | ±0.01 |
| .XXX | ±0.005 |

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES



VIEW A-A

| | | |
|--|-----------|-------------|
| <p>NOTES:</p> <ol style="list-style-type: none"> UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. DIMENSIONS ARE IN INCHES [mm]. | DWG TITLE | PE7AP150-10 |
| | CAGE CODE | 53919 |
| CAD FILE | 08/22/18 | SCALE N/A |
| SIZE | A | 7361 |

PE PASTERNAK®
 THE ENGINEER'S RF SOURCE
 Pasternack Enterprises, Inc.
 P.O. Box 16759 | Irvine | CA | 92623
 Phone: (949) 261-1920 | Fax: (949) 261-7451
 Website: www.pasternack.com | E-Mail: sales@pasternack.com