

## Outdoor Antenna SATOA-81G81G16C-CMB8 81.6mm x 81.6mm x 16.2mm

#### **Features**

- GPS, WiFi & LTE
- Outdoor Antenna
- 50 Ohm Impedance
- Stable And Reliable Performance
- 1575.42, 698~960/1710~2700MHz, 2400~2483.5/4900~5825MHz

### Applications

- Vehicle Tracking
- Asset Tracking
- GPS Navigation
- Machine To Machine Communication





-1 1 1- 11					_
Electrical Parameters (GPS)	Units	Minimum	Typical	Maximum	Remarks
Frequency Band	MHz	1570.42	1575.42	1580.42	±3MHz
Impedance	Ω		50		
Polarization			RHCP		
Axial Ratio	dB			3	For Dielectric Antenna
Peak Gain	dBi		2		For Dielectric Antenna
VSWR				1.5	For Dielectric Antenna
Peak Gain	dBi	26	28	30	For LNA Antenna
VSWR				2	For LNA Antenna
Noise Figure				1.5	For LNA Antenna
Supply Voltage	V DC	2.2		5	For LNA Antenna
Current Consumption	mΑ			15	For I NA Antenna

Electrical Parameters (LTE)	Units	Minimum	Typical	Maximum	Remarks
Frequency Band	MHz	698		960	
Frequency Band	MHz	1710		2700	
Impedance	Ω		50		
Polarization			Linear		
Peak Gain	dBi		2		At Center Frequency
VSWR				3	At Center Frequency


Electrical Parameters (WiFi)	Units	Minimum	Typical	Maximum	Remarks
Frequency Band	MHz	2400		2483.5	
Frequency Band	MHz	4900		5825	
Impedance	Ω		50		
Polarization			Linear		
Peak Gain	dBi		3		At Center Frequency
VSWR				2	At Center Frequency


Environmental Specifications		Mechanical Specifications		
Operating Temperature	-40°C ~ 85°C	Cable	RG174	
Relative Humidity	Up to 95%	Connector	SMA/FAKRA or Others	
Ingress Protection	IP67	Material	ABS	
Vibration	10 to 55Hz with 1.5mm amplitude 2 hours	Mounting Method	Adhesive/Magnet	





# 81.6mm x 81.6mm x 16.2mm


# 














### www.suntsu.com

Specifications are subject to change without notice.

Suntsu Electronics, Inc. 142 TECHNOLOGY DR., SUITE 150 IRVINE, CA 92618

Call: +1-949-783-7300 | Fax: +1-949-783-7301



81.6mm x 81.6mm x 16.2mm



