

# UTC-318

## 18.5" Ubiquitous Touch Computer UTC-318D with Intel® BayTrail J1900 UTC-318E with Intel® Haswell i5-4300U UTC-318F with Intel® Skylake i5-6300U



### Features

- High performance with low power consumption
- Fanless design for quiet operation
- Built in Intel BayTrail J1900 (UTC-318D), Haswell i5-4300U (UTC-318E) and Skylake i5-6300U (UTC-318F)
- Providing Natural Viewing Experience with 16:9 18.5" Display
- Front panel complies with IP65 protection standard
- Landscape and portrait screen modes support different applications
- VESA 100 mm standard mounting holes for varied mounting demands
- Detachable frame design for panel mount applications



### Introduction


UTC-318 is the multi-purpose all-in-one computing system which equipped with wide format, touch based LCD panel. It is easy to integrate key peripherals and display systems for diversified self-service and interactive signage deploy in different application areas. With the removable frame, the system also could fulfill industries or control system applications with panel mounting design. UTC series touch panel computers are the best investments to enhance user satisfaction, further brand equity, and maximize business profits.

### Specifications

Processor System	CPU	Intel® BayTrail J1900	Intel® Haswell Core i5-4300U	Intel® Skylake Core i5-6300U
	Basic Frequency	2.0 GHz (Quad-Core)	1.9GHz (Duo Core)	2.4GHz (Duo Core)
	L2 Cache	2MB	3MB	
	Memory	1 x SO-DIMM DDR3L 1333 MHz up to 8 GB		1 x SO-DIMM DDR4 2133 MHz up to 16 GB
	HDD	1 x 2.5 internal SATA HDD bay		
	Network	2 x Gigabit Ethernet ports (RJ-45)		
	I/O ports	1 x RS-232	1 x RS-232 (optional CSAFE)	1 x RS-232
		1 x RS-232 / 422 / 485	1 x RS-232/422/485	1 x RS-232/422/485
	Stereo Speaker	5 x USB 2.0 / 1 x USB 3.0	2 x USB 2.0 / 4 x USB 3.0	2 x USB 2.0 / 4 x USB 3.0
		2 x Gigabit Ethernet (RJ-45)	2 x Gigabit Ethernet (RJ-45)	2 x Gigabit Ethernet (RJ-45)
	BUS expansion	1 x HDMI	1 x HDMI	1 x HDMI
		Audio Line-out x 1, Mic-in x 1	1 x RJ-11	1 x RJ-11
	Mounting	1 x RJ-11	Audio Line-out x 1, Mic-in x 1	Audio Line-out x 1, Mic-in x 1
Weight		1W x 2		
OS support	BUS expansion	Full-size MiniPCIe/mSATA		
	Weight	5 kg		
Environmental Specifications	Operating Temperature	0 ~ 40° C (32 ~ 104° F)		
	Relative Humidity	10 ~ 95% @ 40° C non-condensing		
	Vibration	0.5G		
	Shock	10 G peak acceleration (11 msec. duration)		
	EMC/ Safety	CE, FCC, UL, CCC CB,BSMI		
	Front Panel Protection	IP65/ NEMA4 Compliant		
	Power Supply	Input Rating	12 V/7 A (84W ITE Adapter)	12-30V/7A (84W ITE Adapter)
Power consumption		Typical 32W Max. 70W		
LCD Display	Size	18.5" TFT LCD		
	Max Resolution	1366 x 768 (FHD 1920 x 1080 Optional)		
	Max Color	16.7M		
	Pixel Pitch (um)	300(H) x 300(V)		
	Brightness (cd/m²)	250 (Typical)		
Touch Screen	View Angle	170°/160°		
	Type	Analog Resistive 5-wires (Res. Flat Glass) / Projected Capacitive Touch Panel (Pcap. Flat Glass) / Glass Panel		
Touch Screen	Light Transmission	Res. Touch : 80% ± 5% / P-Cap Touch : 90% ± 2%		
	Controller	COM interface / USB interface		

\*UTC-318E preliminary datasheet, specification may vary in final version.

## Dimensions



Unit: mm

## Ordering Information

Part No.	Description
UTC-318DR-ATW0E	18.5" White, Intel® Celeron J1900, Res T/S, 4 GB RAM, IT Adapter
UTC-318DR-ATB0E	18.5" Black, Intel® Celeron J1900, Res T/S, 4 GB RAM, IT Adapter
UTC-318DP-ATW0E	18.5" White, Intel® Celeron J1900, PCap T/S, 4 GB RAM, IT Adapter
UTC-318DP-ATB0E	18.5" Black, Intel® Celeron J1900, PCap T/S, 4 GB RAM, IT Adapter
UTC-318ER-ATW0E	18.5" White, Intel Core i5-4300U, Res T/S 4GB RAM, IT Adapter
UTC-318ER-ATB0E	18.5" Black, Intel Core i5-4300U, Res T/S 4GB RAM, IT Adapter
UTC-318EP-ATW0E	18.5" White, Intel Core i5-4300U, PCap T/S 4GB RAM, IT Adapter
UTC-318EP-ATB0E	18.5" Black, Intel Core i5-4300U, PCap T/S 4GB RAM, IT Adapter
UTC-318FR-ATW0E	18.5" White, Intel Skylake Core i5-6300U, Res T/S 4GB RAM, IT Adapter
UTC-318FR-ATB0E	18.5" Black, Intel Skylake Core i5-6300U, Res T/S 4GB RAM, IT Adapter
UTC-318FP-ATW0E	18.5" White, Intel Skylake Core i5-6300U, PCap T/S 4GB RAM, IT Adapter
UTC-318FP-ATB0E	18.5" Black, Intel Skylake Core i5-6300U, PCap T/S 4GB RAM, IT Adapter


## UTC-318 WiFi Ordering Information

Part No.	Description
UTC-300P-W10E	WiFi Antenna x 2 pcs WiFi Module x 1 pc Screws for module x 2pcs
UTC-300P-W11E	WiFi Antenna x 2 pcs WiFi Module x 1 pc Screws for module x 2pcs Half_Minipcie bracket x 1pc (For Windows 10)

## Installation Accessory

Part No.	Description
UTC-300P-D20E	Desk Stand, Single Color-Silver (UTC-318/UTC-320 series)
UTC-WALL-MOUNT1E	Wall Mount Kit (UTC-315/UTC-318/UTC-320 series)
UTC-WALL-MOUNT2E	Wall Mount Kit (UTC-318/UTC-320 series)
UTC-WALL-MOUNT3E	Wall Mount Kit (UTC-315/UTC-318/UTC-320 series)
UTC-T01-STANDE	Triangle shape floor stand (UTC-315/UTC-318/UTC-320 series)
UTC-H01-STANDE	H-shaped floor stand (UTC-315/UTC-318/UTC-320 series)

## Fully- Integrated I/O



- A. COM1
- B. COM2
- C. Line-out
- D. Mic in
- E. LAN ports x 2
- F. HDMI
- G. USB 2.0 x 5 / USB 3.0 x 1 (UTC-318D)  
USB 2.0 x 2 / USB 3.0 x 4 (UTC-318E/UTC-318F)
- H. RJ-11 (UTC-318E/UTC-318F)
- I. Power button
- J. DC input 12V (UTC-318D)  
12-30V (UTC-318E/UTC-318F)

## Peripherals for UTC-318 series

Part No.	Description
UTC-300P-C20E	5M Camera Module, White, for UTC-318/UTC-320 series
UTC-300P-C21E	5M Camera Module, Black, for UTC-318/UTC-320 series
UTC-300P-M20E	Magnet Strip Reader, White, for UTC-318/UTC-320 series
UTC-300P-M21E	Magnet Strip Reader, Black, for UTC-318/UTC-320 series
UTC-300P-R20E	RFID Reader, White, for UTC-318/UTC-320 series
UTC-300P-R21E	RFID Reader, Black, for UTC-318/UTC-320 series
UTC-300P-S20E	Smart Card Reader, White, for UTC-318/UTC-320 series
UTC-300P-S21E	Smart Card Reader, Black, for UTC-318/UTC-320 series
UTC-300P-BB40E	1D Barcode Reader, Black, for UTC-318/UTC-320 series
UTC-300P-BW40E	1D Barcode Reader, White, for UTC-318/UTC-320 series
UTC-300P-BB41E	2D Barcode Reader, Black, for UTC-318/UTC-320 series
UTC-300P-BW41E	2D Barcode Reader, White, for UTC-318/UTC-320 series

## Power Cord Ordering Information

Part No.	Description
1702002605	Power cord 2P FRANCE 10A/16A 220V 1.83M 90D
1702002600	Power Cord 3P UL/CSA(USA) 125V 10A 1.83M 180D
1700000596-11	Power Cord (China) CCC,10A 250V, 3P 1830mm
1700018704	Power Cord UK BSI 2P 10A 250V 180cm 18AWG