


REV. 0

DCO 141371

| | |
|----------------------|----------------------------|
| COIL: @ 25°C | |
| RESISTANCE | 4000 OHMS ±10% |
| NOMINAL VOLTAGE | 26.5 VDC |
| MUST OPERATE | 12.8 VDC |
| TURN-ON BASE CURRENT | 0.5 mADC |
| MUST RELEASE | 8.0 VDC MAX, 1.37 VDC MIN. |

| | |
|--------------|---------------------------------------|
| ENVIRONMENT: | |
| VIBRATION | 10 CPS TO 3000 CPS @ 30 g's |
| SHOCK | 75 g's 6 MS. DURATION |
| TEMPERATURE | -65 °C TO +125 °C |
| NOTES: | TURN-ON TIME 3.5 MS MAX |
| | TURN-OFF TIME 7.5 MS MAX |
| | CONTACT STABILIZATION TIME 2.0 MS MAX |

CUSTOMER DATA SHEET



TERMINAL VIEW

CONTACT RATING: LOW LEVEL TO 1A
28 VDC RESISTIVE 100,000 OPERATIONS

DR. B.D. 9/20/99

PK 9/20/99

COMMUNICATIONS
INSTRUMENTS, INC.

CUST. OPL
 CUST. NO. M28776/4-022P REV. _____

J1MST RELAY

J1MSWT-26XP