


Semi-conductor relay - SIM-AMS 2 - 2271028

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The illustration shows version SIM-AMS 1

Plug-in base, for standard I/O modules, with different numbers of contacts, can be labeled with marker pins BN or BNB



Key commercial data

Packing unit	1 pc
GTIN	 4 017918 103491
Weight per Piece (excluding packing)	9.87 GRM
Custom tariff number	85369010
Country of origin	Poland

Technical data

Dimensions

Pin dimensions	1,1 x 0,5 mm
Hole diameter	1.4 mm

General

Nominal voltage U_N	250 V AC
Nominal current I_N	5 A
Number of contacts, type	2
Color	green
Insulating material	PA
Standards/regulations	DIN VDE 0110b, Gr. C for 250 V DC

Semi-conductor relay - SIM-AMS 2 - 2271028

Classifications

eCl@ss

eCl@ss 4.0	27371102
eCl@ss 4.1	27371102
eCl@ss 5.0	27371001
eCl@ss 5.1	27371001
eCl@ss 6.0	27371001
eCl@ss 7.0	27371001
eCl@ss 8.0	27371001

ETIM

ETIM 2.0	EC000196
ETIM 3.0	EC000196
ETIM 4.0	EC000196
ETIM 5.0	EC002055

UNSPSC

UNSPSC 6.01	30211916
UNSPSC 7.0901	39121542
UNSPSC 11	39121542
UNSPSC 12.01	39121542
UNSPSC 13.2	39121542

Approvals

Approvals

Approvals

UL Recognized / GOST

Ex Approvals

Approvals submitted

Approval details

Semi-conductor relay - SIM-AMS 2 - 2271028


Approvals

UL Recognized	
Nominal current I _N	5 A
Nominal voltage U _N	300 V

GOST	
------	--

Drawings

Dimensioned drawing



Schematic diagram

