



## N-channel 600 V, 0.260 $\Omega$ typ., 12 A MDmesh™ DM2 Power MOSFET in a TO-220 package

Datasheet - production data



**Figure 1: Internal schematic diagram**



### Features

Order code	V <sub>DS</sub>	R <sub>DS(on)</sub> max.	I <sub>D</sub>
STP18N60DM2	600 V	0.295 $\Omega$	12 A

- Fast-recovery body diode
- Extremely low gate charge and input capacitance
- Low on-resistance
- 100% avalanche tested
- Extremely high dv/dt ruggedness
- Zener-protected

### Applications

- Switching applications

### Description

This high voltage N-channel Power MOSFET is part of the MDmesh™ DM2 fast recovery diode series. It offers very low recovery charge ( $Q_{rr}$ ) and time ( $t_{rr}$ ) combined with low  $R_{DS(on)}$ , rendering it suitable for the most demanding high efficiency converters and ideal for bridge topologies and ZVS phase-shift converters.

**Table 1: Device summary**

Order code	Marking	Package	Packing
STP18N60DM2	18N60DM2	TO-220	Tube

## Contents

<b>1</b>	<b>Electrical ratings .....</b>	<b>3</b>
<b>2</b>	<b>Electrical characteristics .....</b>	<b>4</b>
2.1	Electrical characteristics (curves).....	6
<b>3</b>	<b>Test circuits .....</b>	<b>8</b>
<b>4</b>	<b>Package information .....</b>	<b>9</b>
4.1	TO-220 type A package information.....	10
<b>5</b>	<b>Revision history .....</b>	<b>12</b>

# 1 Electrical ratings

**Table 2: Absolute maximum ratings**

Symbol	Parameter	Value	Unit
$V_{GS}$	Gate-source voltage	$\pm 25$	V
$I_D$	Drain current (continuous) at $T_{case} = 25^\circ\text{C}$	12	A
	Drain current (continuous) at $T_{case} = 100^\circ\text{C}$	7.6	
$I_{DM}^{(1)}$	Drain current (pulsed)	48	A
$P_{TOT}$	Total dissipation at $T_{case} = 25^\circ\text{C}$	90	W
$dv/dt^{(2)}$	Peak diode recovery voltage slope	40	V/ns
	MOSFET $dv/dt$ ruggedness	50	
$T_{stg}$	Storage temperature	-55 to 150	$^\circ\text{C}$
$T_j$	Maximum junction temperature	150	

**Notes:**

(1) Pulse width is limited by safe operating area.

(2)  $I_{SD} \leq 12$  A,  $di/dt \leq 400$  A/ $\mu\text{s}$ ,  $V_{DS(\text{peak})} < V_{(\text{BR})DSS}$ ,  $V_{DD} = 80\%$   $V_{(\text{BR})DSS}$ .(3)  $V_{DS} \leq 480$  V.**Table 3: Thermal data**

Symbol	Parameter	Value	Unit
$R_{thj-case}$	Thermal resistance junction-case	1.39	$^\circ\text{C}/\text{W}$
$R_{thj-amb}$	Thermal resistance junction-ambient	62.5	

**Table 4: Avalanche characteristics**

Symbol	Parameter	Value	Unit
$I_{AR}^{(1)}$	Avalanche current, repetitive or not repetitive	2.5	A
$E_{AR}^{(2)}$	Single pulse avalanche energy	380	mJ

**Notes:**(1) Pulse width is limited by  $T_{j\max}$ .(2) starting  $T_j = 25^\circ\text{C}$ ,  $I_D = I_{AR}$ ,  $V_{DD} = 50$  V.

## 2 Electrical characteristics

( $T_{case} = 25^\circ\text{C}$  unless otherwise specified)

**Table 5: Static**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	$V_{GS} = 0 \text{ V}, I_D = 1 \text{ mA}$	600			V
$I_{DSS}$	Zero gate voltage drain current	$V_{GS} = 0 \text{ V}, V_{DS} = 600 \text{ V}$			1.5	$\mu\text{A}$
		$V_{GS} = 0 \text{ V}, V_{DS} = 600 \text{ V}, T_{case} = 125^\circ\text{C}$			100	
$I_{GSS}$	Gate-body leakage current	$V_{DS} = 0 \text{ V}, V_{GS} = \pm 25 \text{ V}$			$\pm 10$	$\mu\text{A}$
$V_{GS(\text{th})}$	Gate threshold voltage	$V_{DS} = V_{GS}, I_D = 250 \mu\text{A}$	3	4	5	V
$R_{DS(\text{on})}$	Static drain-source on-resistance	$V_{GS} = 10 \text{ V}, I_D = 6 \text{ A}$		0.260	0.295	$\Omega$

**Table 6: Dynamic**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$C_{iss}$	Input capacitance	$V_{DS} = 100 \text{ V}, f = 1 \text{ MHz}, V_{GS} = 0 \text{ V}$	-	800	-	$\text{pF}$
$C_{oss}$	Output capacitance		-	40	-	
$C_{rss}$	Reverse transfer capacitance		-	1.33	-	
$C_{oss \text{ eq.}}^{(1)}$	Equivalent output capacitance	$V_{DS} = 0 \text{ to } 480 \text{ V}, V_{GS} = 0 \text{ V}$	-	80	-	pF
$R_G$	Intrinsic gate resistance	$f = 1 \text{ MHz}, I_D = 0 \text{ A}$	-	5.6	-	$\Omega$
$Q_g$	Total gate charge	$V_{DD} = 480 \text{ V}, I_D = 12 \text{ A}, V_{GS} = 10 \text{ V}$ (see <a href="#">Figure 14: "Gate charge test circuit"</a> )	-	20	-	$\text{nC}$
$Q_{gs}$	Gate-source charge		-	5.2	-	
$Q_{gd}$	Gate-drain charge		-	8.5	-	

**Notes:**

<sup>(1)</sup>  $C_{oss \text{ eq.}}$  is defined as a constant equivalent capacitance giving the same charging time as  $C_{oss}$  when  $V_{DS}$  increases from 0 to 80%  $V_{DSS}$

**Table 7: Switching times**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	$V_{DD} = 300 \text{ V}, I_D = 6 \text{ A}$ $R_G = 4.7 \Omega, V_{GS} = 10 \text{ V}$ (see <a href="#">Figure 13: "Switching times test circuit for resistive load"</a> and <a href="#">Figure 18: "Switching time waveform"</a> )	-	13.5	-	$\text{ns}$
$t_r$	Rise time		-	8	-	
$t_{d(off)}$	Turn-off-delay time		-	9.5	-	
$t_f$	Fall time		-	32.5	-	

Table 8: Source-drain diode







Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$I_{SD}$	Source-drain current		-		12	A
$I_{SDM}^{(1)}$	Source-drain current (pulsed)		-		48	A
$V_{SD}^{(2)}$	Forward on voltage	$V_{GS} = 0 \text{ V}, I_{SD} = 12 \text{ A}$	-		1.6	V
$t_{rr}$	Reverse recovery time	$I_{SD} = 12 \text{ A}, dI/dt = 100 \text{ A}/\mu\text{s}, V_{DD} = 60 \text{ V}$ (see <i>Figure 15: "Test circuit for inductive load switching and diode recovery times"</i> )	-	125		ns
$Q_{rr}$	Reverse recovery charge		-	680		nC
$I_{RRM}$	Reverse recovery current		-	11		A
$t_{rr}$	Reverse recovery time	$I_{SD} = 12 \text{ A}, dI/dt = 100 \text{ A}/\mu\text{s}, V_{DD} = 60 \text{ V}, T_j = 150 \text{ }^\circ\text{C}$ (see <i>Figure 15: "Test circuit for inductive load switching and diode recovery times"</i> )	-	190		ns
$Q_{rr}$	Reverse recovery charge		-	1200		nC
$I_{RRM}$	Reverse recovery current		-	13		A






**Notes:**

(1) Pulse width is limited by safe operating area

(2) Pulse test: pulse duration = 300  $\mu\text{s}$ , duty cycle 1.5%


## 2.1 Electrical characteristics (curves)

**Figure 2: Safe operating area****Figure 3: Thermal impedance****Figure 4: Output characteristics****Figure 5: Transfer characteristics****Figure 6: Gate charge vs gate-source voltage****Figure 7: Static drain-source on-resistance**


**Figure 8: Capacitance variations****Figure 9: Normalized gate threshold voltage vs temperature****Figure 10: Normalized on-resistance vs temperature****Figure 11: Normalized  $V_{(BR)DSS}$  vs temperature****Figure 12: Source-drain diode forward characteristics**

### 3 Test circuits


**Figure 13: Switching times test circuit for resistive load**




**Figure 14: Gate charge test circuit**




**Figure 15: Test circuit for inductive load switching and diode recovery times**




**Figure 16: Unclamped inductive load test circuit**



**Figure 17: Unclamped inductive waveform**



**Figure 18: Switching time waveform**



## 4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com).  
ECOPACK® is an ST trademark.

## 4.1 TO-220 type A package information

Figure 19: TO-220 type A package outline




Table 9: TO-220 type A mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.40		4.60
b	0.61		0.88
b1	1.14		1.70
c	0.48		0.70
D	15.25		15.75
D1		1.27	
E	10		10.40
e	2.40		2.70
e1	4.95		5.15
F	1.23		1.32
H1	6.20		6.60
J1	2.40		2.72
L	13		14
L1	3.50		3.93
L20		16.40	
L30		28.90	
øP	3.75		3.85
Q	2.65		2.95

## 5 Revision history

Table 10: Document revision history

Date	Revision	Changes
01-Apr-2015	1	First release.
21-May-2015	2	Text edits throughout document In Section 2.1 Electrical characteristics (curves): - updated Figure 4: Output characteristics - updated Figure 5: Transfer characteristics

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2015 STMicroelectronics – All rights reserved