



## UltraCap<sup>®</sup>

Module  
110 F/ 56 V

**Series/Type:**

**Ordering code:** B48621A9115Q024

**Date:** March 2005

© EPCOS AG 2005. Reproduction, publication and dissemination of this data sheet, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

### Features

- Screw terminal M8 × 15 (plus), M10 × 15 (minus)
- Active cell voltage balancing
- Case material polyethylene, black
- Power type
- 24 serial single cells of 2700 F
- Maintenance-free
- Short-circuit-proof
- Low ESR due to laser-welded interconnections


### Options

- Passive cell voltage balancing (by resistor)

### Note

- Please pay attention to the safety, transport and waste disposal instructions in chapter "Cautions".

### Dimensional drawing



Dimensions in mm

### Electrical specifications

Rated capacitance	( $T_A = 25\text{ °C}$ ; DCC) <sup>1)</sup>	$C_R$	110	F
Tolerance of $C_R$			-10/+30	%
Rated voltage	( $T_A = 25\text{ °C}$ )	$V_R$	56	V
Capacity			1700	mAh
Specific power	(IEC 62391-2)		1.7	kW/kg
Specific power	(IEC 62391-2)		1.7	kW/l
Stored energy	( $V = V_R$ )	$E$	172480	J
Specific energy	( $V = V_R$ )		2.2	Wh/kg
Specific energy	( $V = V_R$ )		2.1	Wh/l
Surge voltage		$V_{\text{surge}}$	64	V
Maximum series resistance	( $T_A = 25\text{ °C}$ ; 1 kHz)	ESR	5.0	mΩ
Maximum series resistance	( $T_A = 25\text{ °C}$ ; 50 mHz)	ESR <sub>DC</sub>	10.0	mΩ
Weight			22.0	kg
Volume			22.0	l
Operating temperature range		$T_{\text{op}}$	-30/+70	°C
Storage temperature	( $V = 0\text{ V}$ )	$T_{\text{st}}$	-40/+70	°C
Lifetime (hours) <sup>2)</sup>	( $T_A = 25\text{ °C}$ ; $V = V_R$ )		90000	h
Lifetime (cycles) <sup>3)</sup>	( $T_A = 25\text{ °C}$ ; $I = 100\text{ A}$ )		500000	cycles

1) DCC: discharging with constant current.

2) Requirements:  $|\Delta C/C_R| \leq 30\%$ ,  $\text{ESR} \leq 2$  times of specified limit,  $I_{\text{leak}} \leq 2$  times of initial value.

3) Requirements:  $|\Delta C/C_R| \leq 30\%$ ,  $\text{ESR} \leq 2$  times of specified limit,  $I_{\text{leak}} \leq 2$  times of initial value (1 cycle: charging to  $V_R$ , 30 s rest, discharging to  $V_R/2$ , 30 s rest).