



AS-Interface module, 2 safe inputs, black, 4-pole connector with screw terminal and 4-pole connector with spring-type terminal, for front plate mounting

<b>product brand name</b>	SIRIUS ACT
<b>product designation</b>	AS-Interface module
<b>product type designation</b>	3SU1
<b>General technical data</b>	
<b>product function</b>	2F-DI
<b>degree of pollution</b>	3
<b>type of voltage</b>	
• of the operating voltage	DC
• of the input voltage	DC
consumed current maximum	60 mA
<b>protection class IP</b>	IP20, clamping screw tightened
shock resistance for railway applications according to EN 61373	Category 1, Class B
vibration resistance for railway applications according to EN 61373	Category 1, Class B
<b>reference code according to IEC 81346-2</b>	K
<b>Substance Prohibitance (Date)</b>	10/01/2014
<b>design of the slave type</b>	2 F-DI
<b>AS-Interface slave profile</b>	S-0.B.F
<b>ID1 code</b>	0...F
<b>number of AS-i slaves</b>	1
protocol is supported ASIsafe (Safety at work) protocol	Yes
operating voltage rated value	26.5 ... 31.6 V
operating voltage 1 at DC rated value	30 V
<b>Communication/ Protocol</b>	
protocol is supported AS-Interface protocol	Yes
<b>Inputs/ Outputs</b>	
<b>number of digital inputs</b>	
• safety-related	2
<b>Connections/ Terminals</b>	
<b>type of electrical connection</b>	Screw connection + spring-type terminal
<b>type of connectable conductor cross-sections</b>	
• solid without core end processing	1x (0.2 ... 2.5 mm <sup>2</sup> )
• finely stranded with core end processing	1x (0.25 ... 2.5 mm <sup>2</sup> )
• finely stranded without core end processing	1x (0.2 ... 2.5 mm <sup>2</sup> )
• at AWG cables	1x (30 ... 12)
tightening torque with screw-type terminals	0.5 ... 0.6 N·m
<b>Product Function</b>	
suitability for use safety-related circuits	Yes

Safety related data	
<b>Safety Integrity Level (SIL) according to IEC 61508</b>	3
SIL Claim Limit (subsystem) according to EN 62061	SILCL 3
<b>performance level (PL) according to EN ISO 13849-1</b>	e
<b>Safe failure fraction (SFF)</b>	99 %
<b>average diagnostic coverage level (DCavg)</b>	99 %
PFHD with high demand rate according to EN 62061	0.0000000045 1/h
<b>PFDavg with low demand rate according to IEC 61508 category according to EN 954-1</b>	0.000005 4

Ambient conditions	
<b>ambient temperature</b>	
<ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> </ul>	-25 ... +70 °C -40 ... +80 °C
environmental category during operation according to IEC 60721	3M6, 3S2, 3B2, 3C3 (without salt spray), 3K6 (with relative humidity of 10 ... 95%, no condensation in operation permitted)

Installation/ mounting/ dimensions	
<b>fastening method</b>	
<ul style="list-style-type: none"> <li>of modules and accessories</li> <li>of AS-i slaves</li> </ul>	Front plate mounting Frontplattenbefestigung
<b>height</b>	42 mm
<b>width</b>	30 mm
<b>depth</b>	65.5 mm

Certificates/ approvals			
General Product Approval	EMC	Functional Safety/Safety of Machinery	Declaration of Conformity

[Confirmation](#)



[Type Examination Certificate](#)



Declaration of Conformity	Test Certificates	other
---------------------------	-------------------	-------



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



[Environmental Conformations](#)

[Confirmation](#)

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1400-1EA10-2AA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1400-1EA10-2AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1400-1EA10-2AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1400-1EA10-2AA0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1400-1EA10-2AA0&lang=en)

-K1

AS-i Bus:  
Slave:



F-IN1

F-IN2

AS-i Fault **Logic**

A schematic symbol for a normally open contact, consisting of a horizontal line with two short vertical lines extending upwards from its ends.

1 ASI+

2 ASI-

3 ASI+

4 ASI-

ADDR

last modified:

12/16/2020