

XN0NE92

Silicon P-channel MOSFET (FET)
Silicon epitaxial planar type (SBD)

For DC-DC converter

■ Features

- Two elements incorporated into one package
- Reduction of the mounting area and assembly cost by one half
- High-speed switching, low on resistance

■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

	Parameter	Symbol	Rating	Unit
FET	Drain-source surrender voltage	V_{DSS}	-12	V
	Gate-source surrender voltage	V_{GSS}	± 15	V
	Drain current	I_D	-1.2	A
	Peak drain current	I_{DP}	-3	A
	Total power dissipation*	P_T	600	mW
	Channel temperature	T_{ch}	125	$^\circ\text{C}$
	Storage temperature	T_{stg}	-55 to +125	$^\circ\text{C}$
SBD	Reverse voltage	V_R	20	V
	Repetitive peak reverse voltage	V_{RRM}	25	V
	Forward current (Average)	$I_{F(AV)}$	700	mA
	Non-repetitive peak forward surge current	I_{FSM}	2	A


■ Package

- Code
Mini5-G1 (Exclusive use for XN0NE92)
- Pin Name

1: Cathode	4: Source
2: Drain	5: Anode
3: Gate	

■ Marking Symbol: 3F

■ Internal Connection



Note) *: Measuring on ceramic substrate at 15 mm × 15 mm × 0.6 mm

■ Electrical Characteristics $T_a = 25^\circ\text{C} \pm 3^\circ\text{C}$

• FET

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Drain-source surrender voltage	V_{DSS}	$I_C = -1 \text{ mA}, V_{GS} = 0$	-12			V
Drain-source cutoff current	I_{DSS}	$V_{DS} = -10 \text{ V}, V_{GS} = 0$			-1	V
Gate-source cutoff current	I_{GSS}	$V_{GS} = \pm 8 \text{ V}, V_{DS} = 0$			± 10	V
Gate threshold voltage	V_{th}	$V_{DS} = -10 \text{ V}, I_D = -1 \text{ mA}$	-0.4		-1.3	V
Forward transfer admittance*	$ Y_{fs} $	$V_{DS} = -10 \text{ V}, I_D = -800 \text{ mA}$	0.8	1.1		S
Drain-source ON resistance*	$R_{DS(on)}$	$V_{GS} = -4 \text{ V}, I_D = -800 \text{ mA}$		350	450	$\text{m}\Omega$
Turn-on time	t_{on}	$V_{DD} = -10 \text{ V}, R_L = 12.5 \Omega,$		15		ns
Storage time	t_{stg}	$I_D = -800 \text{ mA}, V_{GS} = 0 \text{ V to } -4 \text{ V}$		10		ns
Turn-off time	t_{off}			10		ns

Note) 1. Measuring methods are based on JAPANESE INDUSTRIAL STANDARD JIS C 7030 measuring methods for transistors.

2. Observe precautions for handling. Electrostatic sensitive devices.

3. *: Pulse measurement

■ Electrical Characteristics (continued) $T_a = 25^\circ\text{C} \pm 3^\circ\text{C}$

• SBD

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Forward voltage	V_F	$I_F = 700 \text{ mA}$			0.45	V
Reverse current	I_R	$V_R = 20 \text{ V}$			200	μA
Terminal capacitance	C_t	$V_R = 0, f = 1 \text{ MHz}$		100		pF
Reverse recovery time	t_{rr}	$I_F = I_R = 100 \text{ mA}$ $I_{rr} = 10 \text{ mA}, R_L = 100 \Omega$		7		ns

Note) 1. Measuring methods are based on JAPANESE INDUSTRIAL STANDARD JIS C 7031 Measuring methods for diodes.

2. Schottky barrier diode is frail with static electricity, and it should be kept in safety from shock of static electricity and static electricity level.


Maintenance Discontinued

Please visit following URL about latest information.
<http://panasonic.co.jp/semicon/e-index.html>

Mini5-G1

(Exclusive use for XN0NE92)

Unit: mm



Request for your special attention and precautions in using the technical information and semiconductors described in this book

- (1) If any of the products or technical information described in this book is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially, those with regard to security export control, must be observed.
- (2) The technical information described in this book is intended only to show the main characteristics and application circuit examples of the products, and no license is granted under any intellectual property right or other right owned by our company or any other company. Therefore, no responsibility is assumed by our company as to the infringement upon any such right owned by any other company which may arise as a result of the use of technical information described in this book.
- (3) The products described in this book are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
 - Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
 - Any applications other than the standard applications intended.
- (4) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (5) When designing your equipment, comply with the range of absolute maximum rating and the guaranteed operating conditions (operating power supply voltage and operating environment etc.). Especially, please be careful not to exceed the range of absolute maximum rating on the transient state, such as power-on, power-off and mode-switching. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.
- (6) Comply with the instructions for use in order to prevent breakdown and characteristics change due to external factors (ESD, EOS, thermal stress and mechanical stress) at the time of handling, mounting or at customer's process. When using products for which damp-proof packing is required, satisfy the conditions, such as shelf life and the elapsed time since first opening the packages.
- (7) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of Matsushita Electric Industrial Co., Ltd.

Maintained
Discontinued

Please visit following URL about latest information:
<http://panasonic.co.jp/semicon/e-info/index.html>