


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00025	Connector, dc jack, 5.5x2.1xL17.4 mm, molding style	2	
2	30-00395	Wire, 2C TS, 18 AWG, UL2468, 300V, 80C, 4.4 mm, VW-1, PVC, 87A	1	
3	24-00004	Overmold, PVC	2	



Notes:
Functionally equivalent components may be substituted

Wiring Diagram		
50-00025	wire color	50-00025
center	black with stripe	center
sleeve	black	sleeve

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>		
A	7/28/2017	Initial release	PS <small>Digitally signed by PS Date: 2017.07.28 15:35:01 -07'00'</small>	RoHS compliant Function test: no open, no short circuit, no intermittent			
			Verified: LA <small>Digitally signed by LA Date: 2017.07.28 16:01:30 -07'00'</small>	Description:	A	10-02578	
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Cable, 1830 mm, 5.5x2.1 mm 50-00025 dc jack to same, 18 AWG, UL2468, 30-00395 wire	Scale: 1:1		Sheet 1 of 1