

# FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Test plug, nom. voltage: 400 V, nominal current: 20 A, Rated cross section: 2.5 mm<sup>2</sup>, color: gray



## Commercial data

Item number	1029263
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	BE6114
Catalog page	Page 651 (C-1-2019)
GTIN	4055626531199
Weight per piece (including packing)	22.22 g
Weight per piece (excluding packing)	22.22 g
Customs tariff number	85366990
Country of origin	PL

# FTP-3F/8 - Test plug



1029263

<https://www.phoenixcontact.com/pc/products/1029263>

## Technical data

### Product properties

Product type	Test plug terminal block
--------------	--------------------------

### Electrical properties

Maximum power dissipation for nominal condition	1.02 W
---	--------

### Connection data

Nominal cross section	4 mm <sup>2</sup>
Test socket torque	0.5
Conductor cross section flexible	0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section, flexible [AWG]	24 ... 10 (converted acc. to IEC)
Nominal current	20 A
Maximum load current	20 A
Nominal voltage	400 V
Nominal cross section	2.5 mm <sup>2</sup>

### Material specifications

Color	gray
Flammability rating according to UL 94	V0
Insulating material	PC

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

# FTP-3F/8 - Test plug


1029263

<https://www.phoenixcontact.com/pc/products/1029263>



## Drawings

Circuit diagram



# FTP-3F/8 - Test plug




1029263

<https://www.phoenixcontact.com/pc/products/1029263>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1029263>

 **CSA**  
Approval ID: 13631

 **cUL Recognized**  
Approval ID: FILE E 60425

	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
Use group B	300 V	30 A	-	-
Use group C	300 V	30 A	-	-
Use group F	400 V	30 A	-	-

 **UL Recognized**  
Approval ID: FILE E 60425

	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
Use group B	300 V	30 A	-	-
Use group C	300 V	30 A	-	-
Use group F	400 V	30 A	-	-

**cULus Recognized**

# FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>



## Classifications

### ECLASS

ECLASS-11.0	27440313
ECLASS-13.0	27440313
ECLASS-12.0	27440313

### ETIM

ETIM 8.0	EC002255
----------	----------

### UNSPSC

UNSPSC 21.0	20122000
-------------	----------

# FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>



## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

# FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>



## Accessories

**i** Note: Applying some accessories below might limit this product.

### FBS 2-8 - Plug-in bridge

3030284

<https://www.phoenixcontact.com/pc/products/3030284>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, color: red

**i** Max. current carrying capacity: 24 A

---

### FBS 3-8 - Plug-in bridge

3030297

<https://www.phoenixcontact.com/pc/products/3030297>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, color: red

**i** Max. current carrying capacity: 24 A

# FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>




## FBS 4-8 - Plug-in bridge

3030307

<https://www.phoenixcontact.com/pc/products/3030307>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, color: red

 Max. current carrying capacity: 24 A

---

## FBS 5-8 - Plug-in bridge

3030310

<https://www.phoenixcontact.com/pc/products/3030310>



Plug-in bridge, pitch: 8.2 mm, number of positions: 5, color: red

 Max. current carrying capacity: 24 A



## FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>


## FBS 6-8 - Plug-in bridge

3032470

<https://www.phoenixcontact.com/pc/products/3032470>



Plug-in bridge, pitch: 8.2 mm, number of positions: 6, color: red

 Max. current carrying capacity: 24 A

---

## FBS 10-8 - Plug-in bridge

3030323

<https://www.phoenixcontact.com/pc/products/3030323>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, color: red

 Max. current carrying capacity: 24 A

# FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>




## FBSRH 2-8 - Short-circuit connector

3033802

<https://www.phoenixcontact.com/pc/products/3033802>



Short-circuit connector, pitch: 8.2 mm, number of positions: 2, color: red

 Max. current carrying capacity: 24 A

---


## FBSRH 3-8 - Short-circuit connector

3033803

<https://www.phoenixcontact.com/pc/products/3033803>



Short-circuit connector, pitch: 8.2 mm, number of positions: 3, color: red

 Max. current carrying capacity: 24 A

# FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>



## FBSRH 4-8 - Short-circuit connector

3033804

<https://www.phoenixcontact.com/pc/products/3033804>



Short-circuit connector, pitch: 8.2 mm, number of positions: 4, color: red

 Max. current carrying capacity: 24 A

---


## FBS 1/3-8 - Plug-in bridge

3032363

<https://www.phoenixcontact.com/pc/products/3032363>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, pin assignment: 1,3, color: red

 Max. current carrying capacity: 24 A

# FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>




## FBS 2-8 CT - Plug-in bridge

3033830

<https://www.phoenixcontact.com/pc/products/3033830>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, color: orange

 Max. current carrying capacity: 24 A

---

## FBS 3-8 CT - Plug-in bridge

3033831

<https://www.phoenixcontact.com/pc/products/3033831>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, color: orange

 Max. current carrying capacity: 24 A

## FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>


## FBS 4-8 CT - Plug-in bridge

3033832

<https://www.phoenixcontact.com/pc/products/3033832>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, color: orange

 Max. current carrying capacity: 24 A

---

## FBS 10-8 CT - Plug-in bridge

3033833

<https://www.phoenixcontact.com/pc/products/3033833>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, color: orange

 Max. current carrying capacity: 24 A

# FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>




## FBS 2-8 BU - Plug-in bridge

3032567

<https://www.phoenixcontact.com/pc/products/3032567>



Plug-in bridge, pitch: 8.2 mm, number of positions: 2, color: blue

 Max. current carrying capacity: 24 A

---

## FBS 3-8 BU - Plug-in bridge

3032570

<https://www.phoenixcontact.com/pc/products/3032570>



Plug-in bridge, pitch: 8.2 mm, number of positions: 3, color: blue

 Max. current carrying capacity: 24 A

# FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>




## FBS 4-8 BU - Plug-in bridge

3032583

<https://www.phoenixcontact.com/pc/products/3032583>



Plug-in bridge, pitch: 8.2 mm, number of positions: 4, color: blue

 Max. current carrying capacity: 24 A

---


## FBS 5-8 BU - Plug-in bridge

3032596

<https://www.phoenixcontact.com/pc/products/3032596>



Plug-in bridge, pitch: 8.2 mm, number of positions: 5, color: blue

 Max. current carrying capacity: 24 A

## FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>



## FBS 6-8 BU - Plug-in bridge

3032677

<https://www.phoenixcontact.com/pc/products/3032677>



Plug-in bridge, pitch: 8.2 mm, number of positions: 6, color: blue

 Max. current carrying capacity: 24 A

---

## FBS 10-8 BU - Plug-in bridge

3032606

<https://www.phoenixcontact.com/pc/products/3032606>



Plug-in bridge, pitch: 8.2 mm, number of positions: 10, color: blue

 Max. current carrying capacity: 24 A



## FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>



## BTFE 6-3/8 - Test terminal strip

1029246

<https://www.phoenixcontact.com/pc/products/1029246>



Test terminal strip, nom. voltage: 400 V, nominal current: 24 A, number of positions: 8, connection method: Ring cable lug, 1 level, Rated cross section: 6 mm<sup>2</sup>, mounting type: Wall mounting, color: gray

---

## FAME-BAG 260 - Shoulder bag

3069520

<https://www.phoenixcontact.com/pc/products/3069520>



Shoulder bag, For FAME connectors with a width of up to 261 mm, length: 220 mm, width: 290 mm, height: 220 mm, color: black

# FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>



## TMT (EX6,2)R - Marker for terminal blocks

0803063

<https://www.phoenixcontact.com/pc/products/0803063>



Marker for terminal blocks, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: snapped, snap into flat marker groove, lettering field size: 6.2 x 50000 mm, Number of individual labels: 1

---

## US-TMF 100 - Marker for terminal blocks

0829260

<https://www.phoenixcontact.com/pc/products/0829260>



Marker for terminal blocks, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, snap into flat marker groove, lettering field size: 104 x 6.6 mm, Number of individual labels: 20

## FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>



## SF-SL 0,6X3,5-200 - Screwdriver

1212550

<https://www.phoenixcontact.com/pc/products/1212550>



Screwdriver, slot-headed, size: 0.6 x 3.5 x 200 mm, 2-component grip, with non-slip grip

---

## PSBJ-URTK 6 FARBLOS - Female test connector

3026450

<https://www.phoenixcontact.com/pc/products/3026450>



Female test connector, number of positions: 1, color: transparent

## FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>



## PSBJ-URTK 6 RD - Female test connector

3026719

<https://www.phoenixcontact.com/pc/products/3026719>



Female test connector, number of positions: 1, color: red

---

## PSBJ-URTK 6 BU - Female test connector

3026434

<https://www.phoenixcontact.com/pc/products/3026434>



Female test connector, number of positions: 1, color: blue

## FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>



## PSBJ-URTK 6 YE - Female test connector

3026405

<https://www.phoenixcontact.com/pc/products/3026405>



Female test connector, number of positions: 1, color: yellow

---

## PSBJ-URTK 6 GN - Female test connector

3026418

<https://www.phoenixcontact.com/pc/products/3026418>



Female test connector, number of positions: 1, color: green

## FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>



## PSBJ-URTK 6 VT - Female test connector

3026421

<https://www.phoenixcontact.com/pc/products/3026421>



Female test connector, number of positions: 1, color: violet

---

## PSBJ-URTK 6 GY - Female test connector

3026612

<https://www.phoenixcontact.com/pc/products/3026612>



Female test connector, number of positions: 1, color: gray

## FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>



## PSBJ-URTK 6 BK - Female test connector

3026447

<https://www.phoenixcontact.com/pc/products/3026447>



Female test connector, number of positions: 1, color: black

---

## PSBJ-URTK 6 BN - Female test connector

3026971

<https://www.phoenixcontact.com/pc/products/3026971>



Female test connector, number of positions: 1, color: brown

## FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>



## PSBJ-URTK 6 WH - Female test connector

3026448

<https://www.phoenixcontact.com/pc/products/3026448>



Female test connector, number of positions: 1, color: white

---

## ZBF 8:UNBEDRUCKT - Zack Marker strip, flat

0808781

<https://www.phoenixcontact.com/pc/products/0808781>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8 mm, lettering field size: 5.15 x 8.15 mm, Number of individual labels: 10



## FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>



## ZBF 8 CUS - Zack Marker strip, flat

0825030

<https://www.phoenixcontact.com/pc/products/0825030>



Zack Marker strip, flat, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8 mm, lettering field size: 5.15 x 8.15 mm, Number of individual labels: 10

---

## ZBF 8,LGS:FORTL.ZAHLEN - Zack Marker strip, flat

0808804

<https://www.phoenixcontact.com/pc/products/0808804>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 101 ... 110, mounting type: snapped, for terminal block width: 8 mm, lettering field size: 5.15 x 8.15 mm, Number of individual labels: 10

# FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>



## UC-TMF 8 - Marker for terminal blocks

0818137

<https://www.phoenixcontact.com/pc/products/0818137>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 5.1 mm, Number of individual labels: 56

---

## UC-TMF 8 CUS - Marker for terminal blocks

0824654

<https://www.phoenixcontact.com/pc/products/0824654>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 5.1 mm, Number of individual labels: 56

# FTP-3F/8 - Test plug

1029263

<https://www.phoenixcontact.com/pc/products/1029263>



## UCT-TMF 8 - Marker for terminal blocks

0828748

<https://www.phoenixcontact.com/pc/products/0828748>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.4 x 4.7 mm, Number of individual labels: 42

---

## UCT-TMF 8 CUS - Marker for terminal blocks

0829672

<https://www.phoenixcontact.com/pc/products/0829672>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 8.2 mm, lettering field size: 7.4 x 4.7 mm, Number of individual labels: 42

---

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)