

SFSA240GM2AK1TO-C-8C-126-STD
SFSA240GM2AK1TO-I-8C-126-STD
SFSA480GM2AK2TO-C-8C-226-STD
SFSA240GM2AK4TO-C-6B-626-STD
SFSA240GM2AK4TO-I-6B-626-STD


Type	SATA: M.2	SATA: M.2	SATA: M.2	SATA: M.2	SATA: M.2
Product Family	X-75	X-75	X-75	X-75	X-75
Flash Type	3D TLC	3D TLC	3D TLC	3D TLC	3D TLC
Density	240 GB	240 GB	480 GB	240 GB	240 GB
Temp. Grade	0 to 70°C	-40 to 85°C	0 to 70°C	0 to 70°C	-40 to 85°C
Status	in Production	in Production	in Production	in Production	in Production
For new design	Yes	Yes	Yes	Yes	Yes
Rel Cost	1	1	1	1	1
Online Availability					
Endurance Rnd.	2	2	2	2	2
Endurance Seq.	2	2	2	2	2
Perf. Seq. RD [MB/s]	565	565	565	565	565
Perf. Seq. WR [MB/s]	290	290	490	285	285
Perf. Rnd. RD [IOPS]	65400	65400	73700	69300	69300

	SFSA240GM2AK1TO-C-8C-126-STD	SFSA240GM2AK1TO-I-8C-126-STD	SFSA480GM2AK2TO-C-8C-226-STD	SFSA240GM2AK4TO-C-6B-626-STD	SFSA240GM2AK4TO-I-6B-626-STD
Perf. Rnd. WR [IOPS]	69600	69600	70500	67800	67800