


PLASTIC INFRARED LIGHT EMITTING DIODE


QED522 QED523

PACKAGE DIMENSIONS




NOTES:

1. Dimensions for all drawings are in inches (mm).
2. Tolerance of $\pm .010$ (.25) on all non-nominal dimensions unless otherwise specified.



SCHEMATIC



DESCRIPTION

The QED522/523 is an 880 nm AlGaAs LED encapsulated in a clear, peach tinted, plastic TO-46 package.

FEATURES

- $\lambda = 880$ nm
- Chip material = AlGaAs
- Package type: Plastic TO-46
- Matched Photosensor: QSD722/723/724
- Narrow Emission Angle, 20°
- High Output Power
- Package material and color: clear, peach tinted, plastic

PLASTIC INFRARED LIGHT EMITTING DIODE

QED522 QED523

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise specified)

| Parameter | Symbol | Rating | Unit |
|---|--------------------|----------------|------------------|
| Operating Temperature | T_{OPR} | -40 to + 100 | $^\circ\text{C}$ |
| Storage Temperature | T_{STG} | -40 to + 100 | $^\circ\text{C}$ |
| Soldering Temperature (Iron) ^(2,3,4) | $T_{\text{SOL-I}}$ | 240 for 5 sec | $^\circ\text{C}$ |
| Soldering Temperature (Flow) ^(2,3) | $T_{\text{SOL-F}}$ | 260 for 10 sec | $^\circ\text{C}$ |
| Continuous Forward Current | I_F | 100 | mA |
| Reverse Voltage | V_R | 5 | V |
| Power Dissipation ⁽¹⁾ | P_D | 200 | mW |

NOTES:

1. Derate power dissipation linearly 2.67 mW/ $^\circ\text{C}$ above 25 $^\circ\text{C}$.
2. RMA flux is recommended.
3. Methanol or isopropyl alcohols are recommended as cleaning agents.
4. Soldering iron 1/16" (1.6 mm) minimum from housing

ELECTRICAL / OPTICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)

| Parameter | Test Conditions | Symbol | Min | Typ | Max | Units |
|--------------------------|--|-----------------------|-----|-----|-----|---------------|
| Peak Emission Wavelength | $I_F = 100 \text{ mA}$ | λ_{PE} | — | 880 | — | nm |
| Emission Angle | $I_F = 100 \text{ mA}$ | $2\theta_{1/2}$ | — | 20 | — | Deg. |
| Forward Voltage | $I_F = 100 \text{ mA}$, $t_p = 20 \text{ ms}$ | V_F | — | — | 1.8 | V |
| Reverse Current | $V_R = 5 \text{ V}$ | I_R | — | — | 10 | μA |
| Radiant Intensity QEC522 | $I_F = 100 \text{ mA}$, $t_p = 20 \text{ ms}$ | I_E | 20 | — | 80 | mW/sr |
| Radiant Intensity QEC523 | $I_F = 100 \text{ mA}$, $t_p = 20 \text{ ms}$ | I_E | 40 | — | — | mW/sr |
| Rise Time | $I_F = 100 \text{ mA}$ | t_r | — | 800 | — | ns |
| Fall Time | | t_f | — | 800 | — | ns |

PLASTIC INFRARED LIGHT EMITTING DIODE

QED522 QED523

Fig. 1 Normalized Radiant Intensity vs. Forward Current




Fig. 2 Forward Voltage vs. Ambient Temperature




Fig. 3 Normalized Radiant Intensity vs. Wavelength





Fig. 4 Radiation Diagram





PLASTIC INFRARED LIGHT EMITTING DIODE

QED522 QED523

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.