

# Special Function – Alternating

## R66 Series (Includes RLY300)


### Features

- For Duplex Loads
- Transient Protection
- LED Indicates Output Relay Status
- Compact 8-Pin Octal Plug-In Case




### OPERATION

Alternating Relays are used in special applications where the optimization of load usage is required by equalizing the run time of two loads. This alternating action is initiated by a control switch, such as a float switch, manual switch, timing relay, pressure switch, or other isolated contact. Each time the initiating switch is opened, the relay contacts will change state alternating the two loads.



Alternating Relays with cross-wired contacts can operate as normal alternating relays when one control switch is used. If a second lag switch is used, the relay will simultaneously operate two loads on a first ON, last OFF basis.





\* With voltage applied

### AC OPERATED


NTE Type No.	Nom. Voltage	Input Current	Contact Arr.	Max. Contact Cur. @ 30VDC or 240VAC	Diag No.
RLY314	24VAC	125mA	SPDT	10A	D60
R66-5A10-120	120VAC	25mA	SPDT	10A	D60
R66-5A10-240	240VAC	125mA	SPDT	10A	D60
RLY352	24VAC	125mA	DPDT (Cross-Wired)	10A	D60
R66-11CA10-120	120VAC	25mA	DPDT (Cross-Wired)	10A	D60
R66-11CA10-240	240VAC	125mA	DPDT (Cross-Wired)	10A	D60

## Alternating, 10 Amp, AC, SPDT & DPDT Cross-Wired Contact Relays.


### D60



### SPDT, 1 Form "C"



### DPDT Cross-Wired 2 Form "C"



## Electrical Specifications

### Contact

**Rating:** 10 Amps resistive at 240VAC, 1/2 HP at 240VAC, 10 Amps resistive at 30VDC  
**Life:** 500,000 operations at full load  
**Mechanical Life:** 7,000,000 operations at no load

### Operational Characteristics

**Voltage Tolerances:** +10%, -15% at 50/60Hz  
**Power Required:** 3VA

### Protection

**Transient:** 10,000V for 20μs  
**Indicator LED:** 2 LED's marked LOAD A and LOAD B

### Environmental Characteristics

**Operating:** -28°C to +65°C

### ACCESSORIES

MOUNTING STYLES	DESCRIPTION	NTE TYPE NO.
SURFACE MOUNT	8-PIN OCTAL	R95-101
PANEL MOUNT	8-PIN OCTAL	R95-118
DIN RAIL MOUNT	8-PIN OCTAL	R95-113