

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	
▽					▽					
▽					▽					
▽					▽					
APPLICABLE STANDARD										
	OPERATING TEMPERATURE RANGE	-55 °C TO +85 °C			STORAGE TEMPERATURE RANGE	— °C TO — °C				
	RATING VOLTAGE	—			OPERATING HUMIDITY RANGE	— % TO — %				
	CURRENT	—			APPLICABLE CABLE	DIAMETER MAX φ 6.0				
SPECIFICATIONS										
ITEM	TEST METHOD				REQUIREMENTS				QT/AT	
CONSTRUCTION					GENERAL EXAMINATION					
VISUALLY AND BY MEASURING INSTRUMENT.					CONFIRMED VISUALLY.					
MARKING					CONFIRMED VISUALLY.					
MECHANICAL CHARACTERISTICS										
VIBRATION	FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.75 mm, — m/s ² AT 2 h, FOR 3 DIRECTIONS.				NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.				○	—
SHOCK	490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 6 DIRECTIONS.								○	—
ENVIRONMENTAL CHARACTERISTICS										
RAPID CHANGE OF TEMPERATURE	TEMPERATURE TIME -55 → 5~35 → 85 → 5~35 °C 30 → 2~3 → 30 → 2~3 min				NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.				○	—
CORROSION SALT MIST	UNDER 5 CYCLES. EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.				NO HEAVY CORROSION.				○	—
REMARKS										
DRAWN					DESIGNED					
<i>M. Miyazawa</i>					<i>M. Miyazawa</i>					
CHECKED					APPROVED					
<i>J. Sasaki</i>					<i>H. Mizuta</i>					
RELEASED										
Unless otherwise specified, refer to JIS C 5402.										
Note QT:Qualification Test AT:Assurance Test O:Applicable Test										
HRS HIROSE ELECTRIC CO., LTD.			SPECIFICATION SHEET			PART NO.				
CODE NO.(OLD)			DRAWING NO.			CODE NO.				
			ELC4-123778-01			CL230				
						DX30M-* *-CV(10)			1/1	

TO
Q1