DWG. NO. SD-54680-002

番号 No.	部品 PART NAME	材質 MATERIAL	仕上げ FINISH
①	リセプタクル　ハウジング RECEPTACLE HOUSING	液晶ポリマー、ガラス充填、自然色（白）、UL94V-0 LIQUID CRYSTAL POLYMER , GLASS FILLED , NATURAL(WHITE), UL94V-0	—#—
②	リセプタクル　カバー RECEPTACLE COVER	液晶ポリマー、ガラス充填、自然色（白）、UL94V-0 LIQUID CRYSTAL POLYMER , GLASS FILLED , NATURAL(WHITE), UL94V-0	—#—
③	リセプタクル　ターミナル RECEPTACLE TERMINAL	りん青銅 PHOSHOR BRONZE	△1.







基板穴推奨寸法（部品実装）
RECOMMENDED P.C.B.LAYOUT (COMPONENT SIDE)



注記
NOTES :

△1. ターミナル　めっき仕様
TERMINAL PLATING
金めっき ： 表参照
GOLD : SEE TABLE
半田めっき：1.0μm MIN.（プレスフィット部）
TIN-LEAD : 1.0μm MIN.(PRESS-FIT AREA)
ニッケルメッキ：2.0μm MIN.（下地めっき）
NICKEL : 2.0μm MIN.(UNDER PLATING)

2. 推奨基板厚：t=1.6, 2.4mm
RECOMMENDED P.C.B. THICKNESS : t=1.6, 2.4mm
3. 適合プラグ：55510-****
APPLICABLE PLUG : 55510-****
△4. 製品番号及びロットナンバー
MATERIAL NO. & LOT.NO.

6	10	11.98	2.0	1.0	0.76	54680-1001	10
					0.38	54680-1000	
C	B	A	Ni（下地メッキ）[μm]	Sn-Pb [μm]	△1. Au [μm]	MATERIAL NO. (ENG NO.)	極数 PIN

MODEL NO. 54680-****

14	NO.		
13	DRWN:		
	CH'K:		
	APPR:		
12	NO.	REVISED	C
	DRWN:	J2003-2691	
	CH'K:	S.HOSHIKAWA '03/04/21	
	APPR:	A.NODA	
11	NO.	REVISED	B
	DRWN:	JD2001-0740	
	CH'K:	YU.HASEGAWA '01/06/07	
	APPR:	A.NODA	
10	NO.	RELEASED	A
	DRWN:	JD2000-0543	
	CH'K:	S.HOSHIKAWA '99/12/02	
	APPR:	A.NODA	
		H.IKESUGI	

DESCRIPTION　REV

MATERIAL 材料 —#—
FINISH 仕上げ —#—
WIRE RANGE 適用電線範囲 —#—
INS. RANGE 被覆外径 —#—

GENERAL TOLERANCES: (UNLESS SPECIFIED) 一般公差

10 UNDER 未満	±0.2
10 OVER 以上　30 UNDER 未満	±0.25
30 OVER 以上	±0.3
ANGLE 角度	±3°

SCALE 2-1　DESIGN UNITS ☒mm ☐INCH
THIRD ANGLE PROJECTION
DIMENSIONS: ☐mm/INCH ☐INCH/mm ☒mm ONLY
SHT　REV
DRAWN BY & DATE
CHECKED BY & DATE A.Noda
APPROVED BY & DATE
CAD FILENAME 54680002.S01
TITLE: MFB B/B CONN. (FB+) R/A REC. POWER ASSY 5ROW P/F TYPE
molex MOLEX INCORPORATED
MATERIAL NO. SEE TABLE
DRAWING NO. SD-54680-002
SHEET NO. 1 OF 1
SIZE B

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

DO NOT SCALE DRAWING

54680002.S01

EN-02J(097) MXJ-54