SIEMENS

Data sheet 6NH9870-1AA00

product type designation



Antenna ANT794-3M

ANT794-3M mobile wireless antenna for 2G, GSM networks, flat antenna for 900/1800/ 1900 MHz; weatherproof for indoor and outer area; 1.2 m Connection cable permanently connected to the antenna; SMA connector; incl. adhesive tape for mounting.

suitability for operation	for indoor and outdoor applications
radio frequencies	
type of wireless network / is supported	GSM
operating frequency	900 MHz, 1800 MHz, 1900 MHz
antenna gain	0 dB
electrical data	
radiation characteristic	directional
antenna gain	0 dB
standing wave ratio (VSWR) / maximum	1.5
type of electrical connection / of the antenna	SMA Connector
design of plug-in connection	male
mechanical data	
material	
of outer shell	ABS Polylac PA-765, light gray (RAL 7035)
ambient conditions	
ambient temperature	
 during operation 	-40 +75 °C
protection class IP	IP64
design, dimensions and weights	
width	70.5 mm
height	20.5 mm
depth	146.5 mm
net weight	130 g
fastening method	screw fixing
fastening method	
 mast mounting 	Yes
 flat roof mounting 	No
wall mounting	Yes
roof mounting	No
directly on the device	No
wire length / of antenna wire	1.2 m
standards, specifications, approvals	
certificate of suitability	
RoHS conformity	Yes
reference code	
 according to IEC 81346-2 	TF
 according to IEC 81346-2:2019 	TFB
further information / internet-Links	

Internet-Link

• to web page: selection aid TIA Selection Tool

• to website: Industrial communication

• to website: Industry Mall

• to website: Information and Download Center

• to website: Image database

to website: CAx-Download-Managerto website: Industry Online Support

last modified:

http://www.siemens.com/snst

http://www.siemens.com/simatic-net

https://mall.industry.siemens.com

http://www.siemens.com/industry/infocenter

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

https://support.industry.siemens.com

11/3/2021