



Restricted to: General Release

USED ON

THIS DRAWING IS A CONTROLLED DOCUMENT.

Part #	L (meters)	L (feet)	MT-RJ SECURE (No Pins), Green		MT-RJ (No Pins), Black	
			IL (dB)	RL (dB)	IL (dB)	RL (dB)
0-6278875-1	0.950 - 1.050	3.11 - 3.44	0.5	20	0.5	20
0-6278875-2	1.950 - 2.050	6.39 - 6.72	0.5	20	0.5	20
0-6278875-3	2.950 - 3.050	9.67 - 10.00	0.5	20	0.5	20
0-6278875-4	3.920 - 4.080	12.86 - 13.38	0.51	20	0.51	20
0-6278875-5	4.920 - 5.080	16.14 - 16.66	0.51	20	0.51	20
0-6278875-6	5.920 - 6.080	19.42 - 19.94	0.51	20	0.51	20
0-6278875-7	6.920 - 7.080	22.70 - 23.22	0.51	20	0.51	20
0-6278875-8	7.920 - 8.080	25.98 - 26.50	0.51	20	0.51	20
0-6278875-9	8.850 - 9.150	29.03 - 30.01	0.51	20	0.51	20
1-6278875-0	9.850 - 10.150	32.31 - 33.30	0.52	20	0.52	20
1-6278875-1	10.850 - 11.150	35.59 - 36.58	0.52	20	0.52	20
1-6278875-2	11.850 - 12.150	38.87 - 39.86	0.52	20	0.52	20
1-6278875-3	12.850 - 13.150	42.15 - 43.14	0.52	20	0.52	20
1-6278875-4	13.850 - 14.150	45.43 - 46.42	0.52	20	0.52	20
1-6278875-5	14.850 - 15.150	48.72 - 49.70	0.52	20	0.52	20
1-6278875-6	15.840 - 16.160	51.96 - 53.01	0.52	20	0.52	20
1-6278875-7	16.830 - 17.170	55.21 - 56.33	0.53	20	0.53	20
1-6278875-8	17.820 - 18.180	58.46 - 59.64	0.53	20	0.53	20
1-6278875-9	18.810 - 19.190	61.71 - 62.95	0.53	20	0.53	20
2-6278875-0	19.800 - 20.200	64.96 - 66.27	0.53	20	0.53	20
2-6278875-1	20.790 - 21.210	68.20 - 69.58	0.53	20	0.53	20
2-6278875-2	21.780 - 22.220	71.45 - 72.90	0.53	20	0.53	20
2-6278875-3	22.770 - 23.230	74.70 - 76.21	0.53	20	0.53	20
2-6278875-4	23.760 - 24.240	77.95 - 79.52	0.54	20	0.54	20
2-6278875-5	24.750 - 25.250	81.20 - 82.84	0.54	20	0.54	20
2-6278875-6	25.740 - 26.260	84.44 - 86.15	0.54	20	0.54	20
2-6278875-7	26.730 - 27.270	87.69 - 89.46	0.54	20	0.54	20
2-6278875-8	27.720 - 28.280	90.94 - 92.78	0.54	20	0.54	20
2-6278875-9	28.710 - 29.290	94.19 - 96.09	0.54	20	0.54	20
3-6278875-0	29.700 - 30.300	97.44 - 99.40	0.55	20	0.55	20
3-6278875-1	30.690 - 31.310	100.68 - 102.72	0.55	20	0.55	20
3-6278875-2	31.680 - 32.320	103.93 - 106.03	0.55	20	0.55	20
3-6278875-3	32.670 - 33.330	107.18 - 109.35	0.55	20	0.55	20
3-6278875-4	33.660 - 34.340	110.43 - 112.66	0.55	20	0.55	20
3-6278875-5	34.650 - 35.350	113.68 - 115.97	0.55	20	0.55	20
3-6278875-6	35.640 - 36.360	116.92 - 119.29	0.55	20	0.55	20
3-6278875-7	36.630 - 37.370	120.17 - 122.60	0.56	20	0.56	20
3-6278875-8	37.620 - 38.380	123.42 - 125.91	0.56	20	0.56	20
3-6278875-9	38.610 - 39.390	126.67 - 129.23	0.56	20	0.56	20
4-6278875-0	39.600 - 40.400	129.92 - 132.54	0.56	20	0.56	20
5-6278875-0	49.500 - 50.500	162.40 - 165.68	0.58	20	0.58	20

Qty	U of M	Description	Item No.
1	piece	HOUSING, CONN, MT-RJ.BLACK	1
2	piece	DUST COVER, MT-RJ	2
2	piece	SPRING, MT-RJ, 3.8 DESIGN	3
2	piece	PIN KEEPER, 3.8MM	4
2	piece	MT-RJ, SPRING PUSH, UNIVERSAL	5
2	piece	CRIMP EYELET, MT-RJ	6
1	piece	MT-RJ Keyed Connector Housing - Green	7
2	piece	MT-RJ FERRULE, THERMOPLAST,MM	8
AR	meter	2 fiber, 50/125, 1.8 mm, Twinzip, Orange, OFNR (Riser)	9
2	piece	MT-RJ TwinZip Bend Limiting Boot, Beige	10
2	piece	Trace Label	11

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS NOT TO BE DISCLOSED TO ANY OTHER PERSONS OR ORGANIZATIONS WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

LOC  
CE  
DIST  
16

Rev Per	EC#	06-020853	9/29/2006	-	MK
P	LTR	REVISION RECORD	DATE	DN	APVD

Customer Print

DIENSIONS: meters

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 P.LC	±	-
1 P.LC	±	-
2 P.LC	±	-
3 P.LC	±	-
4 P.LC	±	-

DIN	Cable Assy Configurator	MATERIAL	-	HEAT TREAT	-
CHK	Michael Kepko				
APVD	Michael Kepko				
NAME	FO C/A - 2 fiber, 50/125, OFNR (Riser) jacket, MT-RJ SECURE (No Pins) to MT-RJ (No Pins)				
SCALE	NTS	SIZE	A2	DRAWING NO	C- 6278875
SHEET	2 of 3	REV	B		

CAC Customer Layout Rev: D

8

7

6

5

4

3

2

1

D

C

B

A

